

ADDITIVE FOR SYNTHETICS

USE RECOMMENDATIONS

Used to accelerate drying and improve the resistance of synthetic enamels and primers.

Chemical Composition Isocyanates and solvents.

APPLICATION DATA

Catalysis and/or Dilution 6 parts by volume of Enamel or Synthetic Primer.
1 parts by volume of Synthetic Additive
Dilute with Thinner 2750 or ECO 2750 to the proper viscosity.

Application Consult the Technical Notice of the product to be applied.

Theoretical Spreading Rate Consult the Technical Notice of the product to be used.

DRYING

Drying time is directly related to temperature and relative humidity. On wet and cold days it tends to be slower and can be accelerated on drying panels or in an oven at 60^o C. Consult the Technical Notice of the product to be used.

SURFACE PREPARATION

Consult the Technical Notice of the product to be used.

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.