

AUTOMOTIVE MASKING LIQUID

USE RECOMMENDATIONS

Used to insulate automotive parts (windows, dashboard, bumpers, hubcaps, door handles), protecting the vehicle from mist or powder caused by sprays generated by paint and primer applications. Eliminates the use of isolation with papers, reducing lost time

Chemical Composition Water, alcohol, additives and dyes.

APPLICATION DATA

Catalysis and/or Dilution Ready to use.

Application

Before taking out the desired amount for application, the product must be homogenized. Apply by roller, brush or spray gun with 40 to 50 lb/in² pressure. The product must be applied in a single thick coat or in 2 thin coats with an interval of 5 to 10 minutes between coats. To remove the Masking, rinse the surface with water and wash it in the usual way, using neutral soap with the help of gloves.

Do not apply on surfaces that have been painted less than 10 days ago. In the case of Synthetic Enamels, we do not recommend application.

It is not recommended to use water-based paints on this product.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

Date: 12/28/2022

SURFACE PREPARATION

The surface to be applied must be dry and clean (free of grease and dirt).

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

Date: 12/28/2022