

## CATALYST FOR POLYURETHANE PRIMER HS FULL 4.1.1

### USE RECOMMENDATIONS

Indicated as component B, for drying Polyurethane Primer HS Full 4.1.1

### APPLICATION DATA

<b>Catalysis and/or Dilution</b>	Consult the Technical Notice of the product to be catalysed.
<b>Application</b>	Consult the Technical Notice of the product to be catalysed.
<b>VOC (g/mL)</b>	580

### DRYING

Consult the Technical Notice of the product to be catalysed.

### SURFACE PREPARATION

Consult the Technical Notice of the product to be catalysed.

### SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

## **COMMENTS**

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The values found for the specific weight and drying tests (with the specified thickness) were obtained in the laboratory at a temperature of 25°C. With temperatures other than those mentioned, the values established above tend to be different from those specified.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.