



## TECHNICAL NOTICE

FR413 (REV. 01)

### PAINT STRIPPING PASTE

#### USE RECOMMENDATIONS

Indicated for removal of old paintwork and repainting, automotive, appliances, hardware and metallic structures in general.

##### Chemical Composition

Chlorinated, aromatic and thickening solvents.

#### APPLICATION DATA

##### Catalysis and/or Dilution

The paint stripper paste is ready to use.

##### Application

Take the paint stripper putty out of the packaging with a brush or spatula and apply over the application site. Wait 10 to 20 minutes or until it reacts. If necessary, apply a second layer. After removing and scraping, wash the part well with water or clean it with Thinner 2750, Thinner Ecoefficient 2750 or Anjo Degreaser Solution. Do not apply to very hot places or under direct sunlight.

The product must be applied in thick layers for its best performance.

##### Theoretical spreading rate:

1.43m<sup>2</sup>/kg of paint stripper

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

Revision date: 12/29/2022

## **SURFACE PREPARATION**

For better performance of the paint stripper, it is advisable to create grooves in the surface of the paint.

## **SAFETY RECOMMENDATION**

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

## **COMMENTS**

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.