

## PLUS FAST FILLER

### USE RECOMMENDATIONS

Indicated for use in automotive refinishing to correct scratches from sandpaper of Plastic Glue Special White and Gray Series, Universal Plastic Glue and Super Light Universal Plastic Glue. Easy to apply, does not curl between coats, dries quickly and is easy to sand. Available in gray color.

#### Chemical Composition

Alkyd resins, mineral fillers, nitrocellulose, additives, inorganic and organic pigments, oxygenated solvents and hydrocarbons.

### APPLICATION DATA

#### Catalysis and/or Dilution

Ready to use.

#### Application

Apply with a steel or plastic spatula, in thin layers with intervals of 1 to 3 minutes between coats. Plus Fast Filler cannot be applied to bare metal as it does not adhere. It should not be applied in thick layers.

#### Spreading Rate

May vary depending on the application

### DRYING

Air drying time for sanding is 2 hours. Sand with 240-400 wet dry sandpaper.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

## **SURFACE PREPARATION**

With the Plastic Glue already applied, sanded and clean, apply the Plus Fast Filler. In the case of areas where the sheet metal is exposed, it is advisable to apply Anjo Wash Primer.

## **SAFETY RECOMMENDATION**

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

## **COMMENTS**

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.