

PREMIUM RUBBERIZED PRIMER

USE RECOMMENDATIONS

Monocomponent product with low aggressiveness due to solubility in water. Provides texture, giving the part an original appearance. It has excellent drying properties compared to water-based rubber seal treatments on the market.

Indicated for the industry of wooden artifacts, speakers, car bodies, among others. Product formulated to receive any type of automotive finish on it. Examples include synthetic enamel or nitrocellulose lacquer, without these finishes suffering distortions in their shades.

Chemical Composition

Water-soluble acrylic emulsion, additives and special pigments.

APPLICATION DATA

Catalysis and/or Dilution

Premium rubberized primer is ready to use.

Application

Apply with a rubber seal spray gun, with an air pressure of 40 to 70 lb/in² at a distance of 20 to 30 cm from the substrate,

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

DRYING

Drying time to touch is 12 minutes. Drying time for handling is 16 hours. Final drying takes 24 hours. In an oven at 60°C, drying takes 30 to 40 minutes.

SURFACE PREPARATION

Sand or use wire brush to remove rust and loose particles. Use the Anjo Degreaser solution to clean fat, oil, grease and residue in general. When applied to metal surfaces in general, the use of a primer is required to prevent rust; Anjo Green Chromate Zinc Primer or Anjo Anticorrosive Red Oxide Primer can be used.

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.