

## 2 IN 1 WATER BASED POLISHER AND SHINER

### USE RECOMMENDATIONS

Used after polishing with Polishing Wax N°2 Waterborne. Recommended for final polishing of new paintwork or repainting, eliminating light scratches and dent marks, providing high gloss. Does not contain waxes or silicone.

**Chemical Composition** Emollient, Petroleum Distillate, Humectant, Thickener, Abrasive, Preservative and Water.

### APPLICATION DATA

**Catalysis and/or Dilution** Ready to use.

**Application** **For polishing:** Use a polishing machine with a soft pad (sheepskin or synthetic). Work in small areas, adjust machine speed between 1400 – 1800 RPM to control heat generation and result. Apply the product in the center of the pad, spread with the polisher off, then polish using medium contact pressure. Move the polisher slowly and keep the pad clean while polishing.

**For Luster:** Use a polishing machine with a foam pad. Work in small areas, adjust machine speed between 1400 – 1800 RPM to control heat generation and result. Apply the product to the part and spread it with the polisher off, then polish using medium contact pressure. Move the polisher slowly and keep the pad clean while polishing. For best results, spray water to cool the part and to facilitate the cleaning of residues.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

**Spreading Rate**

Polishing – 8 – 10 small cars  
Luster – 20 small cars

**SURFACE PREPARATION**

Make sure the work surface is clean and dry. Do not use on hot surfaces or under direct sunlight. Shake well before using.

**SAFETY RECOMMENDATION**

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

**COMMENTS**

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.