

POLISHING WAX N°2 WATERBORNE

USE RECOMMENDATIONS

Used in the process of general or partial polishing of automotive paints and repainting, removing sanding scratches, chrome parts and other defects in the paint layer, providing intense glossiness. Also indicated to revitalize the glossiness in cases of burnt paint, stains caused by chemical products, acid rain and for polishing high hardness varnishes. No wax and no silicone. Does not stain rubber or plastic parts.

Chemical Composition

Emollient, Petroleum Distillate, Humectant, Thickener, Abrasive, Preservative and Water.

APPLICATION DATA

Catalysis and/or Dilution

Ready to use.

Application

Can be applied using cotton, burlap, flannel or preferably applied with a polishing machine using an abrasive pad (sheepskin or synthetic). Spread the polishing wax well on the surface to be treated, always in small amounts and using a polishing machine, regulated between 1400 and 1800 RPM, with soft and short movements. Repeating the action until the scratches disappear. Residues are easily removed with water or a damp cloth.

Spreading Rate

8 small cars

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

SURFACE PREPARATION

Do not apply under the action of sunlight or heated surfaces, avoiding the formation of stains.

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.