

## RUBBER SEAL (STONING)

### USE RECOMMENDATIONS

Indicated to protect car parts subject to stone impacts and constant impregnation of grease and asphalt residue, such as: internal and external parts of the fenders, front and rear skirts. It eliminates noise when applied to the internal parts of bodywork, trunks, chassis and floors.

This product receives any type of automotive finish on it, that is, synthetic enamel, nitrocellulose lacquer, without these finishes suffering distortions in their shades. We have rubber seal in white and black.

#### Chemical Composition

Water-soluble acrylic emulsion, additives and special pigments.

### APPLICATION DATA

#### Catalysis and/or Dilution

Ready to use, however, if necessary, it can be diluted with water by up to 10%.

#### Application

Apply with a rubber seal spray gun, with an air pressure of 40 lb/in<sup>2</sup> at a distance of 20 to 30 cm from the substrate,

#### Spreading Rate

4 to 5 m<sup>2</sup>/liter/coat

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

## **DRYING**

Drying time to touch is 30 minutes. Drying time for handling is 3 hours. Final drying takes between 12 and 18 hours. In an oven at 60°C, drying takes 30 to 40 minutes.

### **TIP:**

To obtain a rougher and course texture, it is recommended to use a lower air pressure.

## **SURFACE PREPARATION**

Sand or use wire brush to remove rust and loose particles. Use the Anjo Degreaser solution to clean fat, oil, grease and residue in general. Apply rubber seal over the primer to prevent corrosion of the metal part.

## **SAFETY RECOMMENDATION**

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

## **COMMENTS**

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.