

UNIVERSAL PRIMER

USE RECOMMENDATIONS

Product that gives good adhesion, sandability and flexibility to the substrate. Used in the preparation of surfaces that require finishing in nitrocellulose lacquer, polyurethane, polyester and synthetic enamel.

White Universal Primer

Indicated for correcting small pores and as a leveling primer in wood. Indicated to correct imperfections in already prepared bodywork, or to complete the insulation in automotive repainting of surfaces that require finishing. Makes covering light colors easier.

Grey Universal Primer

Indicated for correcting imperfections in already prepared automotive repaint work, or for completing the insulation of surfaces that require finishing.

Chemical Composition

Alkyd resins, mineral fillers, nitrocellulose, additives, inorganic and organic pigments, oxygenated solvents and hydrocarbons.

APPLICATION DATA

Catalysis and/or Dilution

100 parts by volume of Universal Primer.
80 to 100% Thinner 2900 or Eco-efficient 2900.

Application

Apply with a conventional spray gun with a pressure of 40 to 50 lp/in^2 . Apply crossed coats with an interval of 5 to 10 minutes. The Universal Primer has no insulating power, therefore, in the case of applying plastic glues, apply Plus Fast Filler first to correct sandpaper scratches. If Universal Primer

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

is applied directly over the glue and then the finishing paint, mapping will be possible.

Spreading Rate

9 m²/liter/coat

DRYING

Air drying time for sanding is 2 hours. In an oven at 60°C, the drying time is 30 minutes.

SURFACE PREPARATION

Sand the surface to be painted, removing loose parts. Clean the surface with Anjo Degreaser Solution. On metallic surfaces, apply Anjo Wash Primer or an adhesion agent.

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

The use of thinner products other than those specified without prior approval from Anjo may affect product performance and void product warranty.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.