

OCTANO FV POLYESTER FILLER (FIBERGLASS)

USE RECOMMENDATIONS

Used in automotive repainting for repairs, with the purpose of reinforcing fiber parts, ferrous, galvanized, zinc and aluminum surfaces, providing excellent adhesion.

Chemical Composition

Polyester resin, mineral fillers, fiberglass additives, pigments and solvents.

APPLICATION DATA

Catalysis and/or Dilution

100 parts by weight of Octano FV Polyester Filler.
1 to 2 parts by weight of catalyst for Universal Plastic Body Filler and Polyester Filler.

Application

Mix the glue well with the catalyst, and apply with an applicator. Do not reinsert the already prepared mixture into the can. Excessive use of catalyst should be avoided, since possible paint defects such as yellowing and bleeding may occur. To ensure perfect isolation, apply at least 2 crossed coats of PU Anjo Primer, waiting from 5 to 10 minutes between each coat.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

DRYING

After application, let it dry for 20 to 40 minutes and dry sand with 80 and 150 sandpaper and finish with 320 sandpaper.

SURFACE PREPARATION

For application on metallic or non-metallic parts, sand the part with 80 or 150 grit sandpaper to remove rust and traces of peeling paint. To remove paint from the part, Anjo Paint Stripping Paste can be used. On plastic parts, sand with flap 40 sandpaper or carry out manual sanding with 40 sand paper, completely sanding the part where the filler will be applied, then clean with Degreaser Solution to remove dirt, oil, grease and residues in general.

Recommendation: The indication for application in plastic parts is only for small repairs. It is recommended to weld or reinforce the broken spot before applying the filler.

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- This is a flammable product. Keep away from sparks and sources of ignition. Do not smoke at the application site.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

COMMENTS

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.