

Anjo Metallic Spray Paint

Made with high quality products, indicated and approved for indoor use and in crafted objects, decorations, plaster, ceramics, wood, iron, metals, paper, providing a metallic finish. If applied while observing the instructions below, Anjo Metallic Spray Paint ensures good coverage, with high spreading rate and excellent drying.

BASIC PROPERTIES

Color: 13 line colors

Physical State: Liquid / Pressed

Odor: Characteristic

pH: N.A

Flash Point: -70°C (Closed vessel)

Solubility: Insoluble in water

Density: 0.94 g/cm³ to 0.99 g/cm³

Internal Pressure: 45 to 65 Psi at 50°C

Flow Rate: 60 to 100 g/minute

Approximate Spreading rate: 1.0m² to 1.4m² per coat, recommended application 2 to 3 coats.

Drying: to the touch 15 minutes, handling 1 hour, and 24 hours for total curing.

Packaging: 400 ml tube.

INSTRUCTIONS FOR USE

Surface preparation: Sand (if necessary) the part to be applied, removing impurities (dust, waxes, fats, oils, etc.) and any residues.

Application: Shake well before using, make a small test of the applicator pressing the valve a few times against any surface, checking the shape of the jet. Spray from a distance of 10 cm from the site, using uniform movements covering the desired area. For best coverage, apply several coats at regular intervals of 5-15 minutes between coats.

Recommendations: No type of varnish should be used on golden and chrome metallic colors, nor should they be applied on objects that can be handled and or will suffer any type

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

of friction and actions from the weather. On very cold days, it is recommended to leave the pieces to be painted in the sun before painting. Do not carry out the application in closed places or without air circulation. On plastics and acrylics, carry out a test on a small area to check product compatibility and drying. After use, turn the bottle “upside down” and press the valve until you only notice only gas output; this will avoid any clogging. In case of clogging, immerse the applicator nozzle in some type of solvent.

Storage: Keep in a covered and ventilated place (temperature below 50°C). Under these conditions, the product in its original, sealed packaging is guaranteed for 2 years from the date of manufacture.

Precautions: DANGER. Flammable aerosol. Pressurized container: may rupture if heated. May be harmful if swallowed. Causes skin irritation. Causes eye irritation. May cause drowsiness or dizziness. Harmful to aquatic organisms. Keep away from heat, sparks, open flames or hot surfaces. - Do not smoke near the product. Keep out of sunlight. Do not expose to temperatures above 50°C. IN CASE OF SKIN CONTACT: Wash with plenty of soap and water. IN CASE OF CONTACT WITH EYES: Rinse thoroughly with water for several minutes. If you wear contact lenses, remove them if possible. Keep rinsing. **Should not be used on the skin/body.**

Safety: Before using this or any other chemical product, make sure you have read and understood the information contained in the Material Safety Data Sheet (MSDS). Note the potential hazards and follow all precautionary measures, handling instructions, considerations and provisions mentioned on the SDS and on the packaging.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.