

## LINHA EASY ANJOBAG

Graphic ink used in flexographic and gravure machines. Developed for structure of treated low density polyethylene film, treated medium density, treated high density. It has good adhesion, high abrasion resistance, dry blocking resistance with good gloss and good drying.

### RECOMMENDATIONS FOR USE

Easy-to-use ink line in process, exclusive for printing promotional bags or market bags, where no physical-chemical resistance is required. Also suitable for double-sided printing, with a better cost benefit compared to conventional bag lines.

### BASIC PROPERTIES

<b>Color</b>	As per customer standard
<b>Appearance</b>	Viscous liquid
<b>Density (25 °C)</b>	1,00 g/cm <sup>3</sup> (approximate value)
<b>Non-volatile (%)</b>	≥ 20,0 (according to ink)
<b>Viscosity</b>	22 – 26 seconds (Zanh 2)
<b>Drying</b>	As per solicitation o customer
<b>Layout</b>	Ready to use

### APPLICATIONS

<b>Diluition</b>	According to product quality certificate.
<b>Thinner to diluition:</b>	Medium drying Thinner. If other solvents are used, it is advisable to consult the Technical Department.
<b>Auxiliary products</b>	Thinner or solvent Accelerator Thinner or solvent Accelerator

#### ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000 Fax: (48) 3461-8001

[www.anjo.com.br](http://www.anjo.com.br)



## TECHNICAL DATA SHEET

FR413 (REV. 01)

The addition of one of these products to the paint should be corrective.

The addition of retarder or accelerator should not exceed 5% of the ink volume.

### APPLICATION INSTRUCTIONS

Shake the contents with a mechanical stirrer. Make sure no pigment is trapped at the bottom of the container. Adjust the viscosity only after its perfect homogenization. During printing, the reservoir, the inkwell and the tin should remain closed. In stock keep cans tightly closed in a cool and well-ventilated place.

### SAFETY RECOMMENDATION

Store the product in sheltered, ventilated environments.

Flammable product, keep away from sparks, sources of ignition, do not smoke.

Product when applied emanates vapors that should be avoided with the correct use of PPE, such as masks and respirators.

Avoid skin contact using gloves, goggles, proper clothing, protective creams etc. Keep away from contact with children and animals.

### STATUTORY REQUIREMENTS

ANVISA (Brazilian Health Regulatory Agency): Rules heavy metal levels for food packaging that may have contact with children;

FDA (Food and Drug Administration): Norm american regulating foods and drugs for toxicity;

ABRE (Associação Brasileira de Embalagens): Exclusion list to toxicity to ink and solvent the print;

EUPIA (European Printing Ink Association): European exclusion list per toxicity in inks and solvent for printing.

#### ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000 Fax: (48) 3461-8001

[www.anjo.com.br](http://www.anjo.com.br)



## TECHNICAL DATA SHEET

FR413 (REV. 01)

### OBSERVATION

The instructions in this bulletin are based on our experience and technical knowledge, however, some factors are independent of our control as a manufacturer, such as:

substrate treatment, application, working conditions, and so forth. Due to substrate diversity and printing conditions, this sheet is sent for proposed information and is offered without warranty as it must be confirmed by industrial testing before products are used.

Use of thinner other than specified may affect product performance.

Anjo is constantly making improvements to its products and we reserve the right to change the contents of this technical bulletin without prior notice. Anjo is not responsible for improper use of the product.

**Shelf life**      6 months

#### **Packing**

Metal bucket 20 L

Drum 200 L

Metal IBC 1.000 L

**Review**            28/07/2020

#### **ANJO TINTAS**

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000      Fax: (48) 3461-8001

[www.anjo.com.br](http://www.anjo.com.br)