

LINHA 2K ANJORAF

Bi-component ink line for flexography. Suitable for work in conventional woven polypropylene (raffia) and laminate. Indicated for packaging that requires high physical and chemical resistance such as feed, salts and pesticides.

PROPERTIES

- Excellent resistance to abrasion and friction;
- Promotes excellent chemical resistance to packaging;
- Excellent mechanical resistance;
- Higher brightness than conventional lines;
- Great printability and drying.

For extremely aggressive products, we recommend the application of product 041627-00 FX VERNIZ OVER PRINT 2K ANJORAF.

CATALYSIS

Use **8%** of the ink mass of product **041628-00 CATALISADOR 2K ANJORAF** or the catalysis of the system. Product life of 8 hours after its catalysis.

Cutting/trimming cure: 2 hours

Cure for maximum performance (physical and chemical resistance): 72 hours

APPLICATION INSTRUCTIONS

Shake the contents if possible with a mechanical stirrer. Make sure it is very homogeneous and nothing is trapped in the bottom of the container. During printing, the reservoir, ink cartridge and can must remain closed. In stock, keep the container tightly closed, in a cool and ventilated place.

After printing, clean the anilox immediately. Products 003324-00 ACETATO DE ETILA or 019807-00 FX THINNER ACELERADOR 85% are recommended.

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000 Fax: (48) 3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

SAFETY RECOMMENDATION

Store the product in sheltered, ventilated environments.

Flammable product, keep away from sparks, sources of ignition, do not smoke.

Product when applied emanates vapors that should be avoided with the correct use of PPE, such as masks and respirators.

Avoid skin contact using gloves, goggles, proper clothing, protective creams etc.

Keep away from contact with children and animals.

STATUTORY REQUIREMENTS

ANVISA (Brazilian Health Regulatory Agency): Rules heavy metal levels for food packaging that may have contact with children;

FDA (Food and Drug Administration): Norm american regulating foods and drugs for toxicity;

ABRE (Associação Brasileira de Embalagens): Exclusion list to toxicity to ink and solvent the print;

EUPIA (European Printing Ink Association): European exclusion list per toxicity in inks and solvent for printing.

OBSERVATION

The instructions in this bulletin are based on our experience and technical knowledge, however, some factors are independent of our control as a manufacturer, such as:

substrate treatment, application, working conditions, and so forth. Due to substrate diversity and printing conditions, this sheet is sent for proposed information and is offered without warranty as it must be confirmed by industrial testing before products are used.

Use of thinner other than specified may affect product performance.

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000 Fax: (48) 3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

Anjo is constantly making improvements to its products and we reserve the right to change the contents of this technical bulletin without prior notice. Anjo is not responsible for improper use of the product.

Shelf life 6 months

Packing

Metal bucket 20 L

Drum 200 L

Metal IBC 1.000 L

Review 28/07/2020

ANJO TINTAS

UNIDADE IV – IMPRESSÃO

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça - SC - CEP: 88830-000

Fones: (48) 3461-8000 Fax: (48) 3461-8001

www.anjo.com.br