

CATALISADOR COATING PK3000

Auxiliary product indicated for catalysis of Coating PK3000. It has good gloss and good mechanical properties.

CODE: 019615-00

TYPICAL PROPERTIES

Product type	Mixture
Nonvolatile contente	75 ± 1 % (2,2 g / 120 min / 100 ° C)
Viscosity by 23 ° C	160 ± 50 mPa · s
Color (Hazen)	≤ 40
Monomeric HDI	<0,38%

APPLICATION

The solutions formed should be tested for their storage and stability. Only solvents with a maximum of 0.05% water should be used, absence of reactive groups, such as hydroxyl or amino groups, Butyl Acetate and ethyl. Acetate is not recommended as major soil or solvent for thinning as, low solids, may result in lack of product stability. The product must not be diluted below a solids content of 40%.

Extended storage of a solution with less sandpaper content can result in turbidity and sedimentation.

APPLICATION INSTRUCTIONS

Shake the contents if possible with a mechanical stirrer. Make sure no pigment is trapped at the bottom of the container. Adjust the viscosity of the paint only after its perfect homogenization. During printing, the reservoir, the inkwell and the tin

ANJO TINTAS

Unit IV – ANJOPRINT

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça – SC/Brasil - CEP: 88830-000

Tel: +55.48.3461-8000 Fax: +55.48.3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

should remain closed. In stock, keep cans tightly closed, in a cool, well-ventilated place.

SAFETY RECOMMENDATION

Store the product in sheltered, ventilated environments..

Flammable product, keep away from sparks, sources of ignition, do not smoke.

Product when applied emanates vapors that should be avoided with the correct use of PPE, such as masks and respirators.

Avoid skin contact using gloves, goggles, proper clothing, protective creams etc..

Keep away from contact with children and animals.

STATUTORY REQUIREMENTS

The products marketed the ANJO, meet the norm: ANVISA (Brazilian Health Regulatory Agency): Rules heavy metal levels for food packaging that may have contact with children; FDA (Food and Drug Administration): Norm american regulating foods and drugs for toxicity; ABRE (Associação Brasileira de Embalagens): Exclusion list to toxicity to inkd and solvete the print; EUPIA (European Printing Ink Association): European exclusion list per toxicity in inks and solvent for printing.

OBSERVATION

The instructions in this bulletin are based on our experience and technical knowledge, however, some factors are independent of our control as a manufacturer, such as: substrate treatment, application, working conditions, and so forth. Due to substrate diversity and printing conditions, this sheet is sent for proposed information and is offered without warranty as it must be confirmed by industrial testing before products are used.

ANJO TINTAS

Unit IV – ANJOPRINT

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça – SC/Brasil - CEP: 88830-000

Tel: +55.48.3461-8000 Fax: +55.48.3461-8001

www.anjo.com.br



TECHNICAL DATA SHEET

FR413 (REV. 01)

Use of thinner other than specified may affect product performance.

Anjo is constantly making improvements to its products and we reserve the right to change the contents of this technical bulletin without prior notice. Anjo is not responsible for improper use of the product.

Validity	6 months
Packing	
Bucket	17 kg
Revision	31/07/2020

ANJO TINTAS

Unit IV – ANJOPRINT

Rod. SC 108, s/n - km 366 - B. São Simão - Morro da Fumaça – SC/Brasil - CEP: 88830-000

Tel: +55.48.3461-8000 Fax: +55.48.3461-8001

www.anjo.com.br