

In accordance with Globally Harmonized System of
Classification and Labelling of Chemicals (GHS)-
Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 1/8

1 - IDENTIFICATION

| | |
|----------------------------------|---|
| GHS Product identifier: | BASE C - RUBBERIZED PAINT |
| Other means of identification: | 028184-00 |
| Recommended use of the chemical: | Roofs and Facades. |
| Specific restrictions on use: | There are not known restrictions on use of the product. |
| Supplier's details: | ANJO QUIMICA DO BRASIL LTDA |
| Address: | Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800, Criciúma - SC - BR |
| Phone number(s): | (48) 34618000 (48) 34618049 |
| Emergency phone number: | CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252 |

2 - HAZARD IDENTIFICATION

| | |
|---|--|
| Classification of the substance or mixture: | Skin Sensitization - Category 1A Hazardous to the Aquatic Environment - Acute Hazard - Category 3 Hazardous to the Aquatic Environment - Chronic Hazard - Category 3 |
| Classification system adopted: | Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations. |

GHS label elements, including precautionary statements

Pictograms:



Signal word: WARNING

Hazard statement(s): H317 May cause an allergic skin reaction.
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s): **PREVENTION:**
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

RESPONSE TO EMERGENCY:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P321 Specific treatment.
P362 + P364 Take off contaminated clothing. And wash it before reuse.

DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 2/8

Other hazards which do not result in classification: The product has no other hazards.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURE

Components contributing to the hazard: Titanium dioxide (CAS 13463-67-7): 5.10 - 15.30 % ¹;
Hydrated aluminum silicate (CAS 1332-58-7): 2.16 - 6.49 % ¹;
KAOLIN (CAS 1332-58-7): 0.85 - 2.55 % ¹;
2-butoxyethanol (CAS 111-76-2): 0.75 - 2.25 % ²;
Sodium nitrite (CAS 7632-00-0): 0.02 - 0.08 %;
1.2-benzisotiazol-3(2h)-ona (CAS 2634-33-5): 0.01 - 0.04 %;
Triethanolamine 85% (CAS 102-71-6): 0.01 - 0.03 % ²;
Morpholine (CAS 110-91-8): 0.01 - 0.03 % ².

¹Ingredient not classified as hazardous by the Classification System used, but has an established occupational exposure limit, according to section 8.

²The ingredient does not contribute to the hazard but has an established occupational exposure limit, according to section 8.

4 - FIRST-AID MEASURES

Routes of exposure

Inhalation: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

Skin: Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.

Eye: Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.

Ingestion: Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

Most important symptoms/effects, acute and delayed: May cause an allergic skin reaction.

Indication of immediate medical attention and special treatment needed, if necessary: Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

5 - FIRE-FIGHTING MEASURES

Extinguishing Media: Appropriate: carbon dioxide (CO₂), foam, water mist and powder.
Inappropriate: water jet directly.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 3/8

Specific hazards arising from the chemical: The combustion of the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide. Vapors may be heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Containers may explode if heated.

Special protective actions for fire-fighters: Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Do not smoke. Avoid exposure to the product. If necessary, use personal protective equipment as described in Section 8.

For emergency responders: Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.

Environmental precautions: Avoid that the spilled material reaches waterways or sewage system.

Method and materials for containment and cleaning up: Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material.

7 - HANDLING AND STORAGE

Precautions for safe handling

Safe handling of the substance or mixture: Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation.

General hygiene: Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom.

Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion: It is not expected that the product presents a fire or explosion hazard. Use personal protective equipment as described in Section 8.

Adequate conditions: Store in a well ventilated place away from sunlight. Keep container closed. Keep away from high temperatures.

Packaging compatibilities: Similar to the original packaging.

Inadequate packaging materials: There are not known unsuitable material of the product.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 4/8

Occupational
exposure limit:

The values below apply to workplaces.

- Triethanolamine 85%:

ACGIH - TLV - TWA: 5 mg/m³.

- Morpholine:

OSHA - PEL - TWA: 20 ppm; 70 mg/m³;

NIOSH - REL - TWA: 20 ppm;

NIOSH - REL - STEL: 30 ppm;

ACGIH - TLV - TWA: 20 ppm.

- 2-butoxyethanol:

OSHA - PEL - TWA: 50 ppm; 240 mg/m³;

NIOSH - REL - TWA: 5 ppm;

ACGIH - TLV - TWA: 20 ppm.

- KAOLIN:

OSHA - PEL - TWA: 15 mg/m³ (TD); 5 mg/m³ (R);

NIOSH - REL - TWA: 10 mg/m³ (TD); 5 mg/m³ (R);

ACGIH - TLV - TWA: 2 mg/m³ (E. R).

- Hydrated aluminum silicate:

OSHA - PEL - TWA: 15 mg/m³ (TD); 5 mg/m³ (R);

NIOSH - REL - TWA: 10 mg/m³ (TD); 5 mg/m³ (R);

ACGIH - TLV - TWA: 2 mg/m³ (E. R).

- Titanium dioxide:

OSHA - PEL - TWA: 15 mg/m³;

NIOSH - REL - TWA: 2.4 mg/m³ (fine); 0.3 mg/m³ (ultrafine); (Ca) (ultrafine particles); (AA); (B63);

ACGIH - TLV - TWA: 10 mg/m³.

TD: Total dust;

E: The value is for particulate matter containing no asbestos and < 1% crystalline silica;

R: Respirable particulate matter;

Ca: Potential occupational carcinogen.

B63: See NIOSH Intelligence Bulletin 63;

AA: See NIOSH REL Appendix A.

Biological limit:

- 2-butoxyethanol:

ACGIH - BEI: Determinant: Butoxyacetic acid (BAA) in urine. Sampling Time: End of shift. Index: 200.00 mg/g creatine.

Other limits and
values:

- 2-butoxyethanol:

IDLH (NIOSH - 2010): 700 ppm.

Appropriate
engineering controls:

Promote mechanical ventilation and exhaust system to outside. These acts help reducing the exposition to the product. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection:

Safety glasses.

Skin protection:

Closed shoes and suitable protective clothing. Appropriate protective gloves.

Respiratory
protection:

A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.

Thermal hazards:

It does not present thermal hazards.

In accordance with Globally Harmonized System of
Classification and Labelling of Chemicals (GHS)-
Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 5/8

9 - PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---|--|
| Aspect: | Liquid, viscous. |
| Color: | Not available. |
| Odour: | Not available. |
| Melting point/freezing point: | Not available. |
| Boiling point or initial boiling point and boiling range: | Not available. |
| Flammability: | Not available. |
| Lower and upper explosion limit/flammability limit: | Not available. |
| Flash point: | Not available. |
| Auto-ignition temperature: | Not available. |
| Decomposition temperature: | Not available. |
| pH: | 8.8 to 9.5. |
| Kinematic viscosity: | Not available. |
| Solubility(ies): | Miscible in water. |
| Partition coefficient n-octanol/water (log value): | Not available. |
| Vapour pressure: | Not available. |
| Relative vapour density: | Not available. |
| Density and/or relative density: | Not available. |
| Particle characteristics: | Not applicable. |
| Other information: | Absolute density: 1.29 to 1.35 g/cm ³ . |

10 - STABILITY AND REACTIVITY

| | |
|----------------|--|
| Reactivity: | Reactivity is not to be expected under normal conditions of temperature and pressure |
| Stability: | Product is stable under normal conditions of temperature and pressure. |
| Possibility of | Triethanolamine 85%: May react dangerously with oxidizing agents, reducing agents, |

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01

Date: 11/10/2021

Pages: 6/8

hazardous reactions: acids, halogenated compounds, metal hydrides and nitriles.
Morpholine: Risk of explosion on contact with nitromethane.
Sodium nitrite: Risk of explosion in contact with strong reducing agents and combustible materials.
2-butoxyethanol: May react dangerously with aluminum and oxidizing agents. May form peroxides in contact with air.

Conditions to avoid: Elevated temperatures. Contact with incompatible materials.

Incompatible material: Acetone, Acids, Cellulose nitrate, Compounds with high affinity for hydroxyl groups, Fluorine, Halogen compounds, Metallic hydride, Nitriles, Oxidizing Agents, Potassium nitrate, Reducing Agents and Strong base.

Hazardous decomposition products: There are no known hazardous decomposition products.

11 - TOXICOLOGICAL INFORMATION

Acute toxicity: Product not classified as acute toxic.
ATEmix Oral: > 5000 mg/kg.
ATEmix Dermal: > 5000 mg/kg.
ATEmix Vapours (4h): > 20 mg/L.
ATEmix Dusts and mists (4h): > 5 mg/L.

Skin corrosion/irritation: It is not expected that the product causes skin irritation.

Serious eye damage/irritation: It is not expected that the product causes eye irritation.

Respiratory or skin sensitization: May cause an allergic skin reaction.
It is not expected that the product causes respiratory sensitization.

Germ cell mutagenicity: It is not expected that the product presents germ cell mutagenicity.

Carcinogenicity: It is not expected that the product presents carcinogenicity.

Reproductive toxicity: It is not expected that the product presents reproductive toxicity.

The ingredient 2-butoxyethanol, classified as reproductive toxicant - category 2, is in concentration < 3% and does not contribute to this classification of the product.

STOT - Single exposure: It is not expected that the product presents specific target organ toxicity by single exposure.

STOT - Repeated exposure: It is not expected that the product presents specific target organ toxicity by repeated exposure.

Aspiration Hazard: It is not expected that the product presents aspiration hazard.

12 - ECOLOGICAL INFORMATION

Toxicity: Harmful to aquatic life with long lasting effects.
Information regarding to :
- Sodium nitrite:
LC₅₀ (*Oncorhynchus mykiss*, 96h): 0.79 mg/L;
LC₅₀ (*Cyprinus carpio*, 96h): 15.4 mg/L.
- 1,2-benzisotiazol-3(2h)-ona:
EC₅₀ (*Acartia tonsa*, 48h): . mg/L.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01 Date: 11/10/2021 Pages: 7/8

| | |
|--------------------------------|---|
| Persistence and degradability: | Due to the lack of data, it is expected that the product presents persistence and it is not considered readily biodegradable. |
| Bioaccumulative potential: | Presents low bioaccumulative potential in aquatic organisms. |
| Mobility in soil: | Not determined. |
| Other adverse effects: | There are not known other environmental effects for this product. |

13 - DISPOSAL CONSIDERATIONS

Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product. Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

14 - TRANSPORT INFORMATION

| | |
|-------------------------------|--|
| Road: | UN - United Nations: Model Regulations: <ul style="list-style-type: none"> • Recommendations on the Transport of Dangerous Goods. |
| Railway regulations: | COTIF - Convention concerning International Carriage by Rail: <ul style="list-style-type: none"> • Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail |
| Sea: | IMO - International Maritime Organization: <ul style="list-style-type: none"> • IMDG Code - International Maritime Dangerous Goods Code. |
| Air: | IATA - International Air Transport Association: <ul style="list-style-type: none"> • DGR - Dangerous Goods Regulation. |
| UN number: | Not classified as hazardous to transport in different modals. |
| Special precautions for user: | Not applicable |

15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated October 2021.

Change Control:

In accordance with Globally Harmonized System of
Classification and Labelling of Chemicals (GHS)-
Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: BASE C - RUBBERIZED PAINT

Revision: 01 Date: 11/10/2021 Pages: 8/8

| Version | Elaboration | Changes |
|---------|-------------|-------------|
| 01 | 10/18/2021 | Elaboration |

Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;
ATEmix - Acute Toxicity Estimate of the mixture;
BEI - Biological Exposure Index;
CAS - Chemical Abstracts Service;
EC - European Community;
EC₅₀ - Effective Concentration 50%;
EEC - European Economic Community;
IDLH - Immediately Dangerous to Life or Health;
LC₅₀ - Lethal Concentration 50%;
NIOSH - National Institute for Occupational Safety and Health;
OSHA - Occupational Safety & Health Administration;
PEL - Permissible Exposure Limit;
REL - Recommended Exposure Limit;
STEL - Short Term Exposure Limit;
TLV - Threshold Limit Value;
TWA - Time Weighted Average;
UN - United Nations.

Bibliographic references:

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based
on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents &
Biological Exposure Indices (BEIs®). Cincinnati-USA, 2020.

REACH - REGISTRATION, EVALUATION, AUTHORIZATION AND RESTRICTION OF CHEMICALS. Commission
Regulation (EC) No 1272/2008 of December 2008 amending and repealing Directives 67/548/EEC and
1999/45/EC, and amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on
the Registration, Evaluation, Authorization and Restriction of Chemicals. Disponível em: < <http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:353:0001:1355:en:PDF> >. Access in: Oct. 2021.