

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 1/8

### 1 - IDENTIFICATION

GHS Product identifier: RUBBERIZED PAINT - GREEN BLOCK

Other means of identification: 000095-00

Recommended use of the chemical: Roofs and Facades.

Restrictions on use: There are not known restrictions on use of the product.

Supplier's details: ANJO QUIMICA DO BRASIL LTDA

Address: Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800, Criciúma - SC - BR

Phone number(s): (48) 34618000 (48) 34618049

Emergency phone number: CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

### 2 - HAZARD IDENTIFICATION

Classification of the substance or mixture: Hazardous to the Aquatic Environment - Acute Hazard - Category 3  
Hazardous to the Aquatic Environment - Chronic Hazard - Category 3  
Skin Corrosion/Irritation - Category 3  
Skin Sensitization - Category 1A  
Specific Target Organ Toxicity - Single Exposure - Category 2

Classification system adopted: Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:



Signal word: WARNING

Hazard statement(s): H316 Causes mild skin irritation.  
H371 May cause an allergic skin reaction.  
H371 May cause damage to the blood, to the central nervous system, to the kidneys and to the liver.  
H412 Harmful to aquatic life with long lasting effects.

Precautionary statement(s): **PREVENTION:**  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 2/8

### RESPONSE TO EMERGENCY:

P302 + P352 IF ON SKIN: Wash with plenty of water.

P308 + P311 IF exposed or concerned: Call a POISON CENTER or a doctor.

P321 Specific treatment.

P332 + P313 If skin irritation occurs: Get medical advice/attention.

P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

P362 + P364 Take off contaminated clothing. And wash it before reuse.

### STORAGE:

P405 Store locked up.

### DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: The product has no other hazards.

## 3 - COMPOSITION/INFORMATION ON INGREDIENTS

### MIXTURE

Components contributing to the hazard: Titanium dioxide (CAS 13463-67-7): 5.10 - 15.30 % <sup>1</sup>;  
Hydrated aluminum silicate (CAS 1332-58-7): 2.16 - 6.49 % <sup>1</sup>;  
KAOLIN (CAS 1332-58-7): 0.85 - 2.55 % <sup>1</sup>;  
2-butoxyethanol (CAS 111-76-2): 0.75 - 2.25 %;  
Sodium nitrite (CAS 7632-00-0): 0.02 - 0.08 %;  
1.2-benzisotiazol-3(2h)-ona (CAS 2634-33-5): 0.01 - 0.04 %;  
Triethanolamine 85% (CAS 102-71-6): 0.01 - 0.03 % <sup>2</sup>;  
Morpholine (CAS 110-91-8): 0.01 - 0.03 % <sup>2</sup>.

<sup>1</sup>Ingredient not classified as hazardous by the Classification System used, but has an established occupational exposure limit, according to section 8.

<sup>2</sup>The ingredient does not contribute to the hazard but has an established occupational exposure limit, according to section 8.

## 4 - FIRST-AID MEASURES

### Routes of exposure

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Skin:** Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.

**Eye:** Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 3/8

TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

Most important symptoms/effects, acute and delayed: May cause an allergic skin reaction. Causes mild skin irritation with redness and dryness. May cause damage to the blood, to the central nervous system, to the kidneys and to the liver.

Indication of immediate medical attention and special treatment needed, if necessary: Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

### 5 - FIRE-FIGHTING MEASURES

Extinguishing Media: Appropriate: carbon dioxide (CO<sub>2</sub>), foam, water mist and powder.  
Inappropriate: water jet directly.

Specific hazards arising from the chemical: The combustion of the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide.  
Vapors may be heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Containers may explode if heated.

Special protective actions for fire-fighters: Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

### 6 - ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel: Do not smoke. Avoid exposure to the product. If necessary, use personal protective equipment as described in Section 8.

**For emergency service personnel:** Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.

Environmental precautions: Avoid that the spilled material reaches waterways or sewage system.

Method and materials for containment and cleaning up: Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material.

### 7 - HANDLING AND STORAGE

#### Precautions for safe handling

Safe handling of the substance or mixture: Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation.

General hygiene: Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom.

#### Conditions for safe storage, including any incompatibilities

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 4/8

**Technical measures for prevention of fire and explosion:** It is not expected that the product presents a fire or explosion hazard. Use personal protective equipment as described in Section 8.

**Adequate conditions:** Store in a well ventilated place away from sunlight. Keep container closed. Keep away from high temperatures.

**Packaging compatibilities:** Similar to the original packaging.

**Inadequate packaging materials:** There are not known unsuitable material of the product.

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Occupational exposure limit:** The values below apply to workplaces.

- Triethanolamine 85%:

ACGIH - TLV - TWA: 5 mg/m<sup>3</sup>.

- Morpholine:

OSHA - PEL - TWA: 20 ppm; 70 mg/m<sup>3</sup>;

NIOSH - REL - TWA: 20 ppm;

NIOSH - REL - STEL: 30 ppm;

ACGIH - TLV - TWA: 20 ppm.

- 2-butoxyethanol:

OSHA - PEL - TWA: 50 ppm; 240 mg/m<sup>3</sup>;

NIOSH - REL - TWA: 5 ppm;

ACGIH - TLV - TWA: 20 ppm.

- KAOLIN:

OSHA - PEL - TWA: 15 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);

NIOSH - REL - TWA: 10 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);

ACGIH - TLV - TWA: 2 mg/m<sup>3</sup> (E. R).

- Hydrated aluminum silicate:

OSHA - PEL - TWA: 15 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);

NIOSH - REL - TWA: 10 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);

ACGIH - TLV - TWA: 2 mg/m<sup>3</sup> (E. R).

- Titanium dioxide:

OSHA - PEL - TWA: 15 mg/m<sup>3</sup>;

NIOSH - REL - TWA: 2.4 mg/m<sup>3</sup> (fine); 0.3 mg/m<sup>3</sup> (ultrafine); (Ca) (ultrafine particles); (AA); (B63);

ACGIH - TLV - TWA: 10 mg/m<sup>3</sup>

TD: Total dust;

E: The value is for particulate matter containing no asbestos and < 1% crystalline silica;

R: Respirable particulate matter;

Ca: Potential occupational carcinogen.

B63: See NIOSH Intelligence Bulletin 63;

AA: See NIOSH REL Appendix A.

**Biological limit:** - 2-butoxyethanol:

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 5/8

	ACGIH - BEI: Determinant: Butoxyacetic acid (BAA) in urine. Sampling Time: End of shift. Index: 200.00 mg/g creatine.
Other limits and values:	- 2-butoxyethanol: IDLH (NIOSH - 2010): 700 ppm.
Appropriate engineering controls:	Promote mechanical ventilation and exhaust system to outside. These acts help reducing the exposition to the product. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.
<b>Individual protection measures, such as personal protective equipment (PPE)</b>	
Eye/face protection:	Safety glasses.
Skin protection:	Closed shoes and suitable protective clothing. Appropriate protective gloves.
Respiratory protection:	A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.
Thermal hazards:	It does not present thermal hazards.

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

Aspect:	Liquid, viscous.
Color:	Not available.
Odour:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flammability:	Not available.
Lower and upper explosion limit/flammability limit:	Not available.
Flash point:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
pH:	8.8 to 9.5.
Kinematic viscosity:	Not available.
Solubility:	Miscible in water.
Partition coefficient n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01 Date: 05/26/2021 Pages: 6/8

Relative vapour density:	Not available.
Density and/or relative density:	Not available.
Particle characteristics:	Not applicable.
Other information:	Absolute density: 1.29 to 1.35 g/cm <sup>3</sup> .

### 10 - STABILITY AND REACTIVITY

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure
Stability:	Product is stable under normal conditions of temperature and pressure.
Possibility of hazardous reactions:	Triethanolamine 85%: May react dangerously with oxidizing agents, reducing agents, acids, halogenated compounds, metal hydrides and nitriles. Morpholine: Risk of explosion on contact with nitromethane. Sodium nitrite: Risk of explosion in contact with strong reducing agents and combustible materials. 2-butoxyethanol: May react dangerously with aluminum and oxidizing agents. May form peroxides in contact with air.
Conditions to avoid:	Elevated temperatures. Contact with incompatible materials.
Incompatible material:	Acetone, Acids, Cellulose nitrate, Compounds with high affinity for hydroxyl groups, Fluorine, Halogen compounds, Metallic hydride, Nitriles, Oxidizing Agents, Potassium nitrate, Reducing Agents and Strong base.
Hazardous decomposition products:	There are no known hazardous decomposition products.

### 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:	It is not expected that the product presents acute toxicity.
Skin corrosion/irritation:	Causes mild skin irritation with redness and dryness.
Serious eye damage/irritation:	It is not expected that the product causes eye irritation.
Respiratory or skin sensitization:	May cause an allergic skin reaction. It is not expected that the product causes respiratory sensitization.
Germ cell mutagenicity:	It is not expected that the product presents germ cell mutagenicity.
Carcinogenicity:	It is not expected that the product presents carcinogenicity.
Reproductive toxicity:	It is not expected that the product presents reproductive toxicity.
STOT - Single exposure:	May cause damage to the blood, central nervous system, kidneys and liver.
STOT - Repeated exposure:	It is not expected that the product presents specific target organ toxicity by repeated exposure.
Aspiration Hazard:	It is not expected that the product presents aspiration hazard.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 7/8

### 12 - ECOLOGICAL INFORMATION

Toxicity:	Harmful to aquatic life with long lasting effects. Information regarding to : - <u>Sodium nitrite</u> : LC <sub>50</sub> ( <i>Oncorhynchus mykiss</i> , 96h): 0.79 mg/L; LC <sub>50</sub> ( <i>Cyprinus carpio</i> , 96h): 15.4 mg/L. - <u>1,2-benzisotiazol-3(2h)-ona</u> : EC <sub>50</sub> ( <i>Acartia tonsa</i> , 48h): . mg/L.
Persistence and degradability:	Due to the lack of data, it is expected that the product presents persistence and it is not considered readily biodegradable.
Bioaccumulative potential:	Presents low bioaccumulative potential in aquatic organisms.
Mobility in soil:	Not determined.
Other adverse effects:	There are not known other environmental effects for this product.

### 13 - DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### 14 - TRANSPORT INFORMATION

<b>Road:</b>	UN - United Nations: Model Regulations: • Recommendations on the Transport of Dangerous Goods.
<b>Railway regulations:</b>	COTIF - Convention concerning International Carriage by Rail: • Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
<b>Sea:</b>	IMO - International Maritime Organization: • IMDG Code - International Maritime Dangerous Goods Code.
<b>Air:</b>	IATA - International Air Transport Association: • DGR - Dangerous Goods Regulation.
UN number:	Not classified as hazardous to transport in different modals.
Special precautions for user:	Not applicable

### 15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### 16 - OTHER INFORMATION

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** RUBBERIZED PAINT - GREEN BLOCK

Revision: 01

Date: 05/26/2021

Pages: 8/8

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated May 2021.

**Change Control:**

Version	Publication Date	Changes
01	05/26/2021	Elaboration

**Abbreviations:**

ACGIH - American Conference of Governmental Industrial Hygienists;  
BEI - Biological Exposure Index;  
CAS - Chemical Abstracts Service;  
EC<sub>50</sub> - Effective Concentration 50%;  
IDLH - Immediately Dangerous to Life or Health;  
LC<sub>50</sub> - Lethal Concentration 50%;  
NIOSH - National Institute for Occupational Safety and Health;  
OSHA - Occupational Safety & Health Administration;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations.

**Bibliographic references:**

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.  
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents & Biological Exposure Indices (BEIs®). Cincinnati-USA, 2020.