

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 1/ 11

1 - IDENTIFICATION

GHS Product identifier: DTM TOPCOAT

Other means of identification: 000048-00

Recommended use of the chemical and restrictions on use: Exterior and interior.

Restrictions on use: There are not known restrictions on use of the product.

Supplier's details: ANJO QUIMICA DO BRASIL LTDA

Address: Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini, CEP: 88818-800, Criciúma - SC - Brasil

Phone number(s): -

Emergency phone number: CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

2 - HAZARD IDENTIFICATION

Classification of the substance or mixture: Flammable Liquids - Category 3
Skin Corrosion/Irritation - Category 2
Eye Damage/Irritation - Category 2B
Sensitization Skin - Category 1
Carcinogenicity - Category 2
Hazardous to the Aquatic Environment - Acute Hazard - Category 2

Classification system adopted: Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

GHS label elements, including precautionary statements

Pictograms:



Signal word: WARNING

Hazard statement(s): H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 2/ 11

H320 Causes eye irritation.
H351 Suspected of causing cancer.
H401 Toxic to aquatic life.

Precautionary
statement(s):

PREVENTION:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 Keep container tightly closed.
P240 Ground and bond container and receiving equipment.
P241 Use explosion-proof electrical, ventilating and lighting equipment.
P242 Use non-sparking tools.
P243 Take action to prevent static discharges.
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P272 Contaminated work clothing should not be allowed out of the workplace.
P273 Avoid release to the environment.
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

RESPONSE:

P302 + P352 IF ON SKIN: Wash with plenty of water.
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
P337 + P313 If eye irritation persists: Get medical advice/attention.
P362 + P364 Take off contaminated clothing. And wash it before reuse. P370 + P378 In case of fire: Use to extinction: foam, water mist, powder and carbon dioxide (CO₂).

STORAGE:

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 3/ 11

P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

DISPOSAL:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: It is not expected that product presents specific hazards.

3 - COMPOSITION/INFORMATION ON INGREDIENTS

MIXTURES

| | |
|--|--|
| Components contributing to the hazard: | Distillates (petroleum), hydrotreated light (CAS 64742-47-8): 20.25 - 60.76% Titanium dioxide (CAS 13463-67-7): 4.50 - 13.50% Xylene (CAS 1330-20-7): 4.15 - 12.46% Naphtha aliphatic medium (CAS 64742-88-7): 0.47 - 1.42% Scinex (CAS 96-29-7): 0.09 - 0.26% Ethanol (CAS 64-17-5): 0.06 - 0.19% Toluene (CAS 108-88-3): 0.02 - 0.05% ¹ Ethylbenzene (CAS 100-41-4): 0.01 - 0.02% ¹ |
|--|--|

¹The ingredient do not contribute to the hazard, but has occupational exposure limit established according to Section 8.

4 - FIRST-AID MEASURES

Routes of exposure

| | |
|-------------|---|
| Inhalation: | Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS. |
| Skin: | Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS. |
| Eye: | Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS. |
| Ingestion: | Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS. |

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 4/ 11

| | |
|---|---|
| Most important symptoms/effects, acute and delayed: | Causes irritation to skin redness, pain and dryness and with eyes redness and tearing. May cause an allergic skin reaction. |
| Indication of immediate medical attention and special treatment needed, if necessary: | Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected site. |

5 - FIRE-FIGHTING MEASURES

| | |
|---|--|
| Suitable extinguishing media: | Appropriate: Compatible with foam, water mist, powder and carbon dioxide (CO ₂) Inappropriate: Water jet directly. |
| Specific hazards arising from the chemical: | The combustion or the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide. Vapors may be heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Containers may explode if heated. |
| Special protective actions for fire-fighters: | Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist. |

6 - ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

| | |
|--|--|
| For non-emergency personnel: | Do not smoke. Avoid exposure to the product. If necessary, use personal protective equipment as described in Section 8. |
| For emergency responders: | Use protective equipment as described in Section 8. |
| Environmental precautions: | Avoid that the spilled material reaches waterways or sewage system. |
| Methods and materials for containment and cleaning up: | Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material. For final destination, proceed pursuant to Section 13 of this SDS. |

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 5/ 11

7 - HANDLING AND STORAGE

Precautions for safe handling

Safe handling of the substance or mixture: Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation.

General hygiene: Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom.

Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion: It is not expected that the product presents a fire or explosion hazard. Use personal protective equipment as described in Section 8.

Adequate conditions: Store in a well ventilated place away from sunlight. Keep container closed. Keep away from high temperatures. Keep stored at room temperature not exceeding 35 C.

Packaging compatibilities: Similar to the original packaging.

8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Occupational exposure limit: -Ethanol:
TLV - STEL (ACGIH, 2015): 1000 ppm.

-Xylene:
TLV - TWA (ACGIH, 2015): 100 ppm
TLV - STEL (ACGIH, 2015): 150 ppm.

-Ethylbenzene:
TLV - TWA (ACGIH, 2012): 20 ppm.

-Toluene:
TLV - TWA (ACGIH, 2012): 20 ppm.

Biological limit: -Xylene:
BEI (ACGIH, 2015): Methylhipuric acids in urine (end of shift): 2.5 g/g creatinine

-Ethylbenzene:
BEI (ACGIH, 2012): Mandelic acid + phenylglyoxylic acid in urine (end of shift): 0.15 g/g creatinine Ns

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 6/ 11

-Toluene:

BEI (ACGIH, 2012): Toluene in blood (Prior to last shift of workweek):
0.02 mg/L

Toluene in urine (end of shift): 0.03 mg/L

o-Cresol in urine (end of shift): 0.3 mg/g creatinine B

Observations:

Ns: The determinant is nonspecific, since it is also observed after exposure to other chemical.

B: The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration which could affect the interpretation of the results. Such background concentrations are incorporated in the BEI value.

Other limits and values:

-Ethanol:

IDLH (NIOSH, 2010): 3300 ppm (LEL)

Appropriate engineering controls:

Promote direct mechanical ventilation and exhaust system to the outside environment. These measures help reduce exposure to product.

Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection: Safety glasses.

Skin protection: Closed shoes and suitable protective clothing. Appropriate protective gloves.

Respiratory protection: A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.

Thermal hazards: Does not present thermal hazards.

9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid viscous

Color: Not available.

Odour: Not available.

Melting point/freezing point: Not available.

Boiling point or initial boiling point and boiling range: Not available.

Flammability: Not applicable.

Lower and upper explosion limit/flammability limit: Not available.

Flash point: 38 C - 100.4 F (closed cup)

In accordance with Globally Harmonized System of
Classification and Labelling of Chemicals (GHS)-
Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 7/ 11

| | |
|--|--|
| Auto-ignition temperature: | Not available. |
| Decomposition temperature: | Not available. |
| pH: | Not available |
| Kinematic viscosity: | Not available. |
| Solubility: | Immiscible in water. |
| Partition coefficient n-octanol/water (log value): | Not available. |
| Vapour pressure: | Not available |
| Density and/or relative density: | Not available |
| Relative vapour density: | Not available |
| Particle characteristics: | Not available |
| Other information: | Absolute density: 1 to 1.1 g/cm ³ . |

10 - STABILITY AND REACTIVITY

| | |
|--|---|
| Reactivity: | Reactivity is not expected under normal conditions of temperature and pressure. |
| Chemical stability: Possibility of hazardous reactions: | Product is stable under normal conditions of temperature and pressure. Xylene: Risk of explosion when in contact with nitric acid and uranium hexafluoride. You could dangerously react with oxidizing agents and sulfuric acid. Ethanol: Can form explosive mixtures with air. Risk of explosion in contact with alkali metals, alkaline oxides and nitric acid. Ethylbenzene: Reacts violently with oxidizing materials. Iso-butyl alcohol: May ignite on contact with chromium trioxide. May react with aluminum at high temperatures, forming hydrogen gas (explosive). Naphtha (petroleum), hydrodesulfurized heavy: Dangerous reactions are not known for the product. |
| Conditions to avoid: Incompatible material: | Elevated temperatures. Contact with incompatible materials. 2,4 dinitrotoluene, nitric acid, sulphuric acid, acids, oxidizing agents, aluminum, ammonia, halogen, alkaline metals, oxygen and concentrated oxygen. |
| Hazardous decomposition products: | There are not known hazardous decomposition products. |

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 8/ 11

11 - TOXICOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Acute toxicity: | Product not classified as acute toxic by oral route. Acute Toxicity Estimate (ATE) ATEm (oral): > 5000 mg/kg |
| Skin corrosion/irritation: | Causes skin irritation with redness, pain and dryness. |
| Serious eye damage/irritation: | Causes eye irritation with redness and tearing. |
| Respiratory or skin sensitization: | May cause an allergic skin reaction. It is not expected that the product presents sensitization respiratory. |
| Germ cell mutagenicity: | It is not expected that the product presents germ cell mutagenicity. |
| Carcinogenicity: | Suspected of causing cancer. |
| Reproductive toxicity: | It is not expected that the product presents reproductive toxicity. |
| STOT - Single exposure: | It is not expected that the product presents specific target organ toxicity by single exposure. |
| STOT - Repeated exposure: | It is expected that the product presents toxicity specific target organ toxicity by repeated exposure. |
| Aspiration Hazard: | It is not expected that the product presents aspiration hazard. |

12 - ECOLOGICAL INFORMATION

| | |
|-----------|---|
| Toxicity: | Toxic to aquatic life. Information regarding to: <u>-Xylene:</u> EC ₅₀ (<i>Crustacea</i> , 48h): 8.5 mg/L LC ₅₀ (<i>Lepomis macrochirus</i> , 96h): 19 mg/L NOEC (<i>Oncorhynchus mykiss</i> , 56 days): > 1 mg/L <u>-Ethylbenzene:</u> LC ₅₀ (<i>Fish</i> , 96h): 4.2 mg/L ErC ₅₀ (<i>Selenastrum capricornutum</i> , 72h): 4.6 mg/L EC ₅₀ (<i>Crustacea</i> , 48h): 4.75 mg/L NOEC (<i>Ceriodaphnia dubia</i> , 7 days): 1 mg/L <u>-Titanium dioxide:</u> ErC ₅₀ (<i>Pseudokirchneriella subcapitata</i> , 72h): 61 mg/l mg/L <u>-Distillates (petroleum), hydrotreated light:</u> EC ₅₀ (<i>Daphnia magna</i> , 48h): 1.4 mg/L LC ₅₀ (<i>Oncorhynchus mykiss</i> , 96h): 2-5 mg/L mg/L <u>-Naphtha aliphatic medium:</u> ErC ₅₀ (Green algae, 96h): > 100 mg/L |
|-----------|---|

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 9/ 11

| | |
|--------------------------------|---|
| | LC ₅₀ (<i>Amphiprion ocellaris</i> , 96h): > 100 mg/L |
| | EC ₅₀ (<i>Acartia tonsa</i> , 48h): 100 mg/L |
| | -Toluene: |
| | EC ₅₀ (<i>Daphnia magna</i> , 48h): 3.78 mg/L |
| | LC ₅₀ (<i>Oncorhynchus kisutch</i> , 96h): 5.5 mg/L |
| Persistence and degradability: | Due to the lack of data, it is expected that the product presents persistence and it is not considered readily biodegradable. |
| Bioaccumulative potential: | It is not expected that the product presents bioaccumulative potential in aquatic organisms. |
| Mobility in soil: | Not determined. |
| Other adverse effects: | There are not known other environmental effects for this product. |

13 - DISPOSAL CONSIDERATIONS

Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product. Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

14 - TRANSPORT INFORMATION

| | |
|-----------------------------|---|
| Road: | <i>UN - "United Nations"</i> <i>Recommendations on the TRANSPORT OF DANGEROUS GOODS. Model Regulations</i> |
| UN number: | 1263 |
| UN Proper Shipping Name: | PAINT RELATED MATERIAL |
| Transport hazard class(es): | 3 |
| Packing group: | II |
| Rail: | <i>Convention concerning International Carriage by Rail (COTIF)</i> <i>Appendix C - Regulations concerning the International Carriage of Dangerous Goods by Rail - RID</i> |
| UN number: | 1263 |
| UN Proper Shipping Name: | PAINT RELATED MATERIAL |
| Transport hazard class(es): | 3 |
| Packing group: | II |

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 10/ 11

Sea: *IMO - International Maritime Organization
International Maritime Dangerous Goods Code (IMDG Code)*

UN number: 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: II

Environmental hazards: *The product is not considered a marine pollutant.*

EmS: F-E,S-E

Air: *IATA - International Air Transport Association
Dangerous Goods Regulation (DGR)*

UN number: 1263

UN proper shipping name: PAINT RELATED MATERIAL

Transport hazard class(es): 3

Packing group: II

Special precautions for user: There is no need of special precautions.

Transport in bulk according to MARPOL 73/78, Annex II, and the IBC Code:

Consult regulations:

- International Maritime Organization. MARPOL: Articles, protocols, annexes, unified interpretations of the International Convention for the Prevention of Pollution from Ships, 1973, as modified by the Protocol of 1978 relating thereto, consolidated edition. IMO, London, 2006.
- International Maritime Organization. IBC code: International code for the construction and equipment of shipping carrying dangerous chemicals in bulk: With Standards and guidelines relevant to the code. IMO, London, 2007.

15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170)

- International Labour Organization, 1990;

International Organization for Standardization - ISO 11014:2009.

16 - OTHER INFORMATION

In accordance with Globally Harmonized System
of Classification and Labelling of Chemicals
(GHS)-Chapter 1.5 and Annex 4

SAFETY DATA SHEET

Product: DTM TOPCOAT

Revision: 02

Date: 2018/07/13

Pages: 11/ 11

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

SDS elaborated in May 2018.

Change control:

| Version | Publication Date | Changes |
|---------|------------------|----------------|
| 02 | 2018/05/22 | New SDS layout |

Abbreviations:

ACGIH - *American Conference of Governmental Industrial Hygienists*

BEI - *Biological Exposure Index*

CAS - *Chemical Abstracts Service*

EC₅₀ - *Effective Concentration 50%*

IDLH - *Immediately Dangerous to Life or Health*

LC₅₀ - *Lethal Concentration 50%*

LEL - *Lower Explosive Limit*

NIOSH - *National Institute for Occupational Safety and Health*

STEL - *Short Term Exposure Limit*

TLV - *Threshold Limit Value*

TWA - *Time Weighted Average*

Bibliographic references:

Globally Harmonized System of Classification and Labelling of Chemicals (GHS). 6. rev. ed.
New York: United Nations, 2015.