

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 1/11

### 1 - IDENTIFICATION

GHS Product identifier:	SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75
Other means of identification:	000511-00
Recommended use of the chemical:	Used for painting.
Specific restrictions on use:	There are not known restrictions on use of the product.
Supplier's details:	ANJO QUIMICA DO BRASIL LTDA
Address:	Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800, Criciúma - SC - BR
Phone number(s):	(48) 34618000 (48) 34618049
Emergency phone number:	CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

### 2 - HAZARD IDENTIFICATION

Classification of the substance or mixture:	Flammable Liquids - Category 3 Skin Corrosion/Irritation - Category 2 Serious eye damage/eye irritation - Category 2A Carcinogenicity - Category 1B Reproductive Toxicity - Category 1A Specific Target Organ Toxicity –Single Exposure - Category 3 - Narcotic and Category 3 - Respiratory Specific Target Organ Toxicity –Repeated Exposure - Category 2 Hazardous to the Aquatic Environment - Acute Hazard - Category 2 Hazardous to the Aquatic Environment - Chronic Hazard - Category 2
Classification system adopted:	Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:



Signal word: DANGER

Hazard statement(s):	H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H350 May cause cancer. H360 May damage fertility or the unborn child. H373 May cause damage to the central nervous system through prolonged or repeated exposure.
----------------------	--

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 2/11

H411 Toxic to aquatic life with long lasting effects.

Precautionary  
statement(s):

**PREVENTION:**

P201 Obtain special instructions before use.  
P202 Do not handle until all safety precautions have been read and understood.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

**RESPONSE TO EMERGENCY:**

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308 + P313 IF exposed or concerned: If eye irritation persists: If skin irritation occurs: Get medical advice/attention.  
P312 Call a POISON CENTER or a doctor, if you feel unwell.  
P314 Get medical advice/attention if you feel unwell.  
P321 Specific treatment.  
P332 + P313 If skin irritation occurs: Get medical advice/attention.  
P337 + P313 If eye irritation persists: If skin irritation occurs: Get medical advice/attention.  
P362 + P364 Take off contaminated clothing. And wash it before reuse.  
P370 + P378 In case of fire: Use [.] to extinguish.  
P391 Collect spillage.

**STORAGE:**

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

**DISPOSITION:**

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which  
do not result in  
classification:

It is not expected that product presents specific hazards.

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 3/11

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

#### MIXTURE

Components contributing to the hazard:

- Distillates (petroleum). hydrotreated light (CAS 64742-47-8): 12.43 - 37.29 %;
- Light naphtha (CAS 64741-66-8): 9.76 - 29.27 %;
- Xylene (CAS 1330-20-7): 7.36 - 22.08 %;
- Yellow transcor  $\gamma$ - 208 (CAS Not applicable): 3.50 - 10.50 %;
- Lead chromate (CAS 1344-37-2): 1.05 - 3.15 %;
- Naphtha aliphatic medium (CAS 64742-88-7): 0.94 - 2.83 %;
- Octoato de cálcio (CAS 136-51-6): 0.34 - 1.02 %;
- Titanium dioxide (CAS 13463-67-7): 0.25 - 0.75 % <sup>1</sup>;
- Quartz (CAS 14808-60-7): 0.12 - 0.37 % <sup>1</sup>;
- 1.2.4-trimethylbenzene (CAS 95-63-6): 0.12 - 0.36 %;
- Scinex (CAS 96-29-7): 0.09 - 0.28 %;
- Scarlet chrome/molybdate orange basil (CAS 12656-85-8): 0.08 - 0.25 %;
- Diethylene glycol butyl ether (CAS 112-34-5): 0.06 - 0.18 %;
- Toluene (CAS 108-88-3): 0.03 - 0.10 % <sup>2</sup>.

<sup>1</sup>Ingredient not classified as hazardous by the Classification System used, but has an established occupational exposure limit, according to section 8.

<sup>2</sup>The ingredient does not contribute to the hazard but has an established occupational exposure limit, according to section 8.

### 4 - FIRST-AID MEASURES

#### Routes of exposure

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Skin:** Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.

**Eye:** Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Most important symptoms/effects, acute and delayed:** Causes skin irritation with redness, pain and dryness. Causes serious eye irritation with redness and pain. May cause drowsiness or dizziness, may cause dizziness and nausea. May cause respiratory irritation, may cause cough and sneezing. May cause damage to the central nervous system through prolonged or repeated exposure.

**Indication of immediate medical attention and special treatment needed, if necessary:** Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

### 5 - FIRE-FIGHTING MEASURES

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 4/11

Extinguishing Media:	Appropriate: Compatible with all means of extinguishing.
Specific hazards arising from the chemical:	The combustion or the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as sparks, open flames or flames of matches and cigarettes, welding operations, pilot lights and electric motors. Can accumulate static charge by flow or agitation. Vapors from heated liquid can be ignited by static discharge. Vapors are heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Can travel great distances causing retrogression of the flame or new fires both in open environments in as confined ones. Containers may explode if heated.
Special protective actions for fire-fighters:	Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

### 6 - ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled material without the use of appropriate clothing. Avoid exposure to the product. Stay in a safe place, with wind from behind. Use personal protective equipment as described in Section 8.
<b>For emergency responders:</b>	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the spilled material reaches waterways or sewage system.
Method and materials for containment and cleaning up:	Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material. For final destination, proceed pursuant to Section 13 of this SDS.

### 7 - HANDLING AND STORAGE

#### Precautions for safe handling

Safe handling of the substance or mixture:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Avoid exposure to the chemical, since the effects may not be felt immediately.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom. Contaminated clothing should be changed and washed before reuse. Remove clothing and protective equipment contaminated before entering eating areas.

#### Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion:	Keep away from heat, sparks, open flames and hot surfaces. - Do not smoke. Keep container tightly closed. Ground the container vessel and the receiver of the product during transfers. Only use anti-sparking tools. Avoid the accumulation of electrostatic
--	---

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 5/11

	charges. Use electrical equipment, ventilation and lighting explosion proof. Use personal protective equipment as described in Section 8.
Adequate conditions:	Store in a well ventilated place, away from sunlight. Keep container closed. Keep away from high temperatures and ignition sources. Keep stored at room temperature not exceeding 35°C (95°F).
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material of the product.

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Occupational exposure limit: The values below apply to workplaces.

- Toluene:  
OSHA - PEL - TWA: (Z2);  
NIOSH - REL - TWA: 375 mg/m<sup>3</sup>; 100 ppm;  
NIOSH - REL - STEL: 560 mg/m<sup>3</sup>; 150 ppm;  
ACGIH - TLV - TWA: 20 ppm.
- Diethylene glycol butyl ether:  
ACGIH - TLV - TWA: 10 ppm (IFV).
- Quartz:  
OSHA - PEL - TWA: (CFR1);  
NIOSH - REL - TWA: 0.05 mg/m<sup>3</sup> (Ca); (AA);  
ACGIH - TLV - TWA: 0.025 mg/m<sup>3</sup> (R).
- Titanium dioxide:  
OSHA - PEL - TWA: 15 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 2.4 mg/m<sup>3</sup> (fine); 0.3 mg/m<sup>3</sup> (ultrafine); (Ca) (ultrafine particles); (AA); (B63);  
ACGIH - TLV - TWA: 10 mg/m<sup>3</sup>.
- Xylene:  
OSHA - PEL - TWA: 100 ppm; 435 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 100 ppm;  
NIOSH - REL - STEL: 150 ppm;  
ACGIH - TLV - TWA: 100 ppm;  
ACGIH - TLV - STEL: 150 ppm.

Z2: See NIOSH REL Annotated Z-2;  
IFV: Inhalable fraction and vapor;  
R: Respirable particulate matter;  
Ca: Potential occupational carcinogen.  
AA: See NIOSH REL Appendix A;  
CFR1: See CFR 1910.1053.  
B63: See NIOSH Intelligence Bulletin 63;.

Biological limit: - Toluene:  
ACGIH - BEI: Determinant: o-Cresol in urine. Sampling Time: End of shift. Index: 0.30 mg/g creatinine. B; Determinant: Toluene in blood. Sampling Time: Prior to last shift of

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 6/11

workweek. Index: 0.02 mg/L; Determinant: Toluene in urine. Sampling Time: End of shift. Index: 0.03 mg/L.

- Xylene:

ACGIH - BEI: Determinant: Methylhippuric acids in urine. Sampling Time: End of shift. Index: 1.50 g/g creatinine.

B: The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration which could affect the interpretation of the results. Such background concentrations are incorporated in the BEI value.

Other limits and values: Not established.

Appropriate engineering controls: Promote mechanical ventilation and exhaust system to outside. These acts help reducing the exposition to the product. Keep atmospheric concentration of the product's components below the exposition occupational limits indicated. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.

### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection: Safety glasses.

Skin protection: Closed shoes and suitable protective clothing. Appropriate protective gloves.

Respiratory protection: A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.

Thermal hazards: Does not present thermal hazards.

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

Aspect: Liquid.

Color: Not available.

Odour: Not available.

Melting point/freezing point: Not available.

Boiling point or initial boiling point and boiling range: Not available.

Flammability: Flammable.

Lower and upper explosion limit/flammability limit: Not available.

Flash point: 38 °C (100.4 °F) - Closed cup.

Auto-ignition temperature: Not available.

Decomposition: Not available.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04 Date: 09/23/2021 Pages: 7/11

temperature:	
pH:	Not available.
Kinematic viscosity:	Not available.
Solubility(ies):	Water immiscible.
Partition coefficient n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Relative vapour density:	Not available.
Density and/or relative density:	Not available.
Particle characteristics:	Not applicable.
Other information:	Absolute density: 0.85 to 1.15.

### 10 - STABILITY AND REACTIVITY

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure
Stability:	Product is stable under normal conditions of temperature and pressure.
Possibility of hazardous reactions:	There are not known hazardous reactions with the product.
Conditions to avoid:	Elevated temperatures. Sources of ignition. Contact with incompatible materials.
Incompatible material:	Acids, Alcohols, Base, Concentrated oxygen, Glycols, Halogen, Ketones, Nitric acid, Oxidizing Agents, Oxygen, Perchloric acid, Peroxides and Sulphuric acid.
Hazardous decomposition products:	There are not known hazardous decomposition products.

### 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:	Product not classified as acute toxic. ATEmix Oral: > 5000 mg/kg. ATEmix Dermal: > 5000 mg/kg. ATEmix Vapours (4h): > 20 mg/L. ATEmix Dusts and mists (4h): > 5 mg/L.
Skin corrosion/irritation:	Causes skin irritation with redness, pain and dryness.
Serious eye damage/irritation:	Causes serious eye irritation with redness and pain.
Respiratory or skin sensitization:	It is not expected that the product presents respiratory or skin sensitization.  The ingredient Scinex, classified as skin sensitizer - category 1, is in concentration < 1% and does not contribute to this classification of the product.
Germ cell	It is not expected that the product presents germ cell mutagenicity.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 8/11

mutagenicity:

**Carcinogenicity:** May cause cancer.

The ingredient Scinex, classified as carcinogenic - category 2, is in concentration < 1% and does not contribute to this classification of the product.

**Reproductive toxicity:**

May damage fertility or the unborn child.

The ingredient Scarlet chrome/molybdate orange basil, classified as reproductive toxicant - category 1A, is in concentration < 0.3% and does not contribute to this classification of the product.

The ingredient Octoato de cálcio, classified as reproductive toxicant - category 2, is in concentration < 3% and does not contribute to this classification of the product.

**STOT - Single exposure:**

May cause drowsiness or dizziness, may cause dizziness and nausea.

May cause respiratory irritation, may cause cough and sneezing.

Information regarding to :

- Xylene:

At high concentrations may cause hypotension, tachycardia, vasodilation, dizziness, incoordination, headache, confusion, stupor and coma.

**STOT - Repeated exposure:**

May cause damage to the central nervous system through prolonged or repeated exposure.

The ingredient Lead chromate, classified as specific target organ toxicant - repeated exposure - category 2, is in concentration < 10% and does not contribute to this classification of the product.

**Aspiration Hazard:** It is not expected that the product presents aspiration hazard.

### 12 - ECOLOGICAL INFORMATION

**Toxicity:**

Toxic to aquatic life with long lasting effects.

Information regarding to :

- Distillates (petroleum), hydrotreated light:

EC<sub>50</sub> (*Daphnia magna*, 48h): 1.4 mg/L;

LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h): 2-5 mg/L.

- Light naphtha:

EC<sub>50</sub> (*Daphnia magna*, 48h): 4.5 mg/L;

LC<sub>50</sub> (*Amphiprion ocellaris*, 96h): 4.5 - 23 mg/L.

- Xylene:

NOEC (*Oncorhynchus mykiss*, 56 d): > 1 mg/L;

NOEC (*Ceriodaphnia dubia*, 7 d): > 1 mg/L;

LC<sub>50</sub> (*Lepomis macrochirus*, 96h): 19 mg/L;

EC<sub>50</sub> (*Crustacea*, 48h): 8.5 mg/L.

- Naphtha aliphatic medium:

LC<sub>50</sub> (*Amphiprion ocellaris*, 96h): > 100 mg/L;

ErC<sub>50</sub> (*Green algae*, 96h): > 100 mg/L;

EC<sub>50</sub> (*Acartia tonsa*, 48h): 100 mg/L.

**Persistence and degradability:**

It is expected that the product presents persistence and it is not considered readily biodegradable.

Information regarding to :

- 1,2,4-trimethylbenzene:

Degradation rate: 4% in 28 days.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04 Date: 09/23/2021 Pages: 9/11

Bioaccumulative potential:	Presents low bioaccumulative potential in aquatic organisms. Information regarding to : - <u>Xylene</u> : BCF: 6 log $K_{ow}$ : 3.09.
Mobility in soil:	Not determined.
Other adverse effects:	There are not known other environmental effects for this product.

### 13 - DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### 14 - TRANSPORT INFORMATION

<b>Road:</b>	UN - United Nations: Model Regulations: • Recommendations on the Transport of Dangerous Goods.
UN number:	1263
Proper shipping name:	PAINT RELATED MATERIAL
Subsidiary risk class or division:	3
Primary risk class or division:	NA
Packing group:	II
<b>Railway regulations:</b>	COTIF - Convention concerning International Carriage by Rail: • Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
UN number:	1263
<b>Sea:</b>	IMO - International Maritime Organization: • IMDG Code - International Maritime Dangerous Goods Code.
UN number:	1263
Proper shipping name:	PAINT RELATED MATERIAL
Subsidiary risk class or division:	3
Primary risk class or division:	NA
Packing group:	II
EmS:	F-E, <u>S</u> -E
Environmental	The product is not considered a marine pollutant for transportation.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 10/11

hazards:

**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Subsidiary risk class or division: 3

Primary risk class or division: NA

Packing group: II

Special precautions for user: Not applicable

### 15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### 16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated September 2021.

#### Change Control:

Version	Elaboration	Changes
04	09/23/2021	Change in composition. Change in section: 1, 2, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 and 16.

#### Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
BCF - Bioconcentration factor;  
BEI - Biological Exposure Index;  
CAS - Chemical Abstracts Service;  
EC<sub>50</sub> - Effective Concentration 50%;  
IARC - International Agency for Research on Cancer;  
K<sub>ow</sub> - Octanol/Water partition coefficient;  
LC<sub>50</sub> - Lethal Concentration 50%;

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** SYNTHETIC ENAMEL ER-PLUS YELLOW CHROME MBB 1700 74/75

Revision: 04

Date: 09/23/2021

Pages: 11/11

NIOSH - National Institute for Occupational Safety and Health;  
NOEC - No Observed Effect Concentration;  
OSHA - Occupational Safety & Health Administration;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations.

### **Bibliographic references:**

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.  
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based  
on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents &  
Biological Exposure Indices (BEIs®). Cincinnati-USA, 2020.

ECHA - EUROPEAN CHEMICAL AGENCY. Available at: < <http://echa.europa.eu/web/guest> >. Access in: Access  
in: Sep. 2021.

GESTIS - SUBSTANCE DATABASE. Available at: < [http://gestis-  
en.itrust.de/nxt/gateway.dll/gestis\\_en/000000.xml?f=templates\\$fn=default.htm\\$3.0](http://gestis-en.itrust.de/nxt/gateway.dll/gestis_en/000000.xml?f=templates$fn=default.htm$3.0) >. Access in: Access in:  
Sep. 2021.

HSDB - HAZARDOUS SUBSTANCES DATA BANK. Available at: [http://toxnet.nlm.nih.gov/cgi-  
bin/sis/htmlgen?HSDB](http://toxnet.nlm.nih.gov/cgi-bin/sis/htmlgen?HSDB). Access in: Sep. 2021.

IARC - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER. Available at:  
<http://monographs.iarc.fr/ENG/Classification/index.php>. Access in: Sep. 2021.

IPCS - INTERNATIONAL PROGRAMME ON CHEMICAL SAFETY - INCHEM. Available at: <http://www.inchem.org/>.  
Access in: Sep. 2021.

IUCLID - INTERNATIONAL UNIFORM CHEMICAL INFORMATION DATABASE. [S.1.]: European chemical Bureau.  
Available at: <http://ecb.jrc.ec.europa.eu>.

NIOSH - NATIONAL INSTITUTE OF OCCUPATIONAL AND SAFETY. International Chemical Safety Cards.  
Available at: <http://www.cdc.gov/niosh/>. Access in: Sep. 2021.

TOXNET - TOXICOLOGY DATA NETWORKING. ChemIDplus Lite. Available at: <http://chem.sis.nlm.nih.gov/>.  
Access in: Sep. 2021.