

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 1/10

### 1 - IDENTIFICATION

GHS Product identifier:	BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW
Other means of identification:	013359-00
Recommended use of the chemical:	Metal enamel.
Specific restrictions on use:	There are not known restrictions on use of the product.
Supplier's details:	ANJO QUIMICA DO BRASIL LTDA
Address:	Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800, Criciúma - SC - BR
Phone number(s):	(48) 34618000 (48) 34618049
Emergency phone number:	CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

### 2 - HAZARD IDENTIFICATION

Classification of the substance or mixture:	Flammable Liquids - Category 3 Skin Corrosion/Irritation - Category 2 Serious eye damage/eye irritation - Category 2A Specific Target Organ Toxicity - Single Exposure - Category 3 - Respiratory Hazardous to the Aquatic Environment - Acute Hazard - Category 1 Hazardous to the Aquatic Environment - Chronic Hazard - Category 1
Classification system adopted:	Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:



Signal word: WARNING

Hazard statement(s):  
H226 Flammable liquid and vapour.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H335 May cause respiratory irritation.  
H410 Very toxic to aquatic life with long lasting effects.

Precautionary statement(s):  
**PREVENTION:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 2/10

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

### RESPONSE TO EMERGENCY:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P319 Get medical help if you feel unwell.  
P321 Specific treatment.  
P332 + P317 If skin irritation occurs: Get medical help.  
P337 + P317 If eye irritation persists: Get medical help.  
P362 + P364 Take off contaminated clothing. And wash it before reuse.  
P370 + P378 In case of fire: Use carbon dioxide (CO<sub>2</sub>), foam, water mist and powder to extinguish.  
P391 Collect spillage.

### STORAGE:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification:

It is not expected that product presents specific hazards.

## 3 - COMPOSITION/INFORMATION ON INGREDIENTS

### MIXTURE

Components contributing to the hazard:	Distillates (petroleum). hydrotreated light (CAS 64742-47-8): 24.20 - 72.59 %; Xylene (CAS 1330-20-7): 7.33 - 22.00 %; Titanium dioxide (CAS 13463-67-7): 0.30 - 0.91 % <sup>1</sup> ; Aluminum (CAS 7429-90-5): 0.29 - 0.86 % <sup>2</sup> ; Quartz (CAS 14808-60-7): 0.21 - 0.62 % <sup>1</sup> ; Scinex (CAS 96-29-7): 0.10 - 0.30 %; Ácido poliéster modificado (CAS Not applicable): 0.07 - 0.21 %; Ethylbenzene (CAS 100-41-4): 0.01 - 0.04 % <sup>3</sup> ; Isobutyl alcohol (CAS 78-83-1): 0.01 - 0.03 %.
--	---

<sup>1</sup>Ingredient not classified as hazardous by the Classification System used, but has an established occupational exposure limit, according to section 8.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 3/10

<sup>2</sup>The hazards arising from the inhalation of this ingredient are not parameters for the classification of the mixture, since, both the physico-chemical characteristics and the adequate understanding of specialists, when a solid ingredient in the form of powder is diluted in a liquid mixture, it's not biologically available to cause its harms.

<sup>3</sup>The ingredient does not contribute to the hazard but has an established occupational exposure limit, according to section 8.

### 4 - FIRST-AID MEASURES

#### Routes of exposure

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Skin:** Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.

**Eye:** Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Most important symptoms/effects, acute and delayed:** Causes skin irritation with redness, pain and dryness. Causes serious eye irritation with redness and pain. May cause respiratory irritation, may cause cough and sneezing.

**Indication of immediate medical attention and special treatment needed, if necessary:** Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

### 5 - FIRE-FIGHTING MEASURES

**Extinguishing Media:** Appropriate: carbon dioxide (CO<sub>2</sub>), foam, water mist and powder. Inappropriate: water jet directly.

**Specific hazards arising from the chemical:** The combustion or the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide. Vapors may be heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Containers may explode if heated.

**Special protective actions for fire-fighters:** Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

### 6 - ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Do not smoke. Avoid exposure to the product. If necessary, use personal protective equipment as described in Section 8.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 4/10

**For emergency responders:** Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.

**Environmental precautions:** Avoid that the spilled material reaches waterways or sewage system.

**Method and materials for containment and cleaning up:** Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material.

### 7 - HANDLING AND STORAGE

#### Precautions for safe handling

**Safe handling of the substance or mixture:** Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation.

**General hygiene:** Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom.

#### Conditions for safe storage, including any incompatibilities

**Technical measures for prevention of fire and explosion:** It is not expected that the product presents a fire or explosion hazard. Use personal protective equipment as described in Section 8.

**Adequate conditions:** Store in a well ventilated place away from sunlight. Keep container closed. Keep away from high temperatures. Keep stored at room temperature not exceeding 35°C (95°F).

**Packaging compatibilities:** Similar to the original packaging.

**Inadequate packaging materials:** There are not known unsuitable material of the product.

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

**Occupational exposure limit:** The values below apply to workplaces.

- Isobutyl alcohol:

OSHA - PEL - TWA: 100 ppm; 300 mg/m<sup>3</sup>;

NIOSH - REL - TWA: 50 ppm;

ACGIH - TLV - TWA: 50 ppm.

- Ethylbenzene:

OSHA - PEL - TWA: 100 ppm; 435 mg/m<sup>3</sup>;

NIOSH - REL - TWA: 100 ppm;

NIOSH - REL - STEL: 125 ppm;

ACGIH - TLV - TWA: 20 ppm.

- Quartz:

OSHA - PEL - TWA: (CFR1);

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 5/10

NIOSH - REL - TWA: 0.05 mg/m<sup>3</sup> (Ca); (AA);  
ACGIH - TLV - TWA: 0.025 mg/m<sup>3</sup> (R).  
- Aluminum:  
OSHA - PEL - TWA: 15 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);  
NIOSH - REL - TWA: 10 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);  
ACGIH - TLV - TWA: 1 mg/m<sup>3</sup> (R).  
- Titanium dioxide:  
OSHA - PEL - TWA: 15 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 2.4 mg/m<sup>3</sup> (fine); 0.3 mg/m<sup>3</sup> (ultrafine); (Ca) (ultrafine particles); (AA); (B63);  
ACGIH - TLV - TWA: 10 mg/m<sup>3</sup>.  
- Xylene:  
OSHA - PEL - TWA: 100 ppm; 435 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 100 ppm;  
NIOSH - REL - STEL: 150 ppm;  
ACGIH - TLV - TWA: 100 ppm;  
ACGIH - TLV - STEL: 150 ppm.

**Biological limit:**  
- Ethylbenzene:  
ACGIH - BEI: Determinant: Sum of mandelic acid and phenylglyoxylic acid in urine. Sampling Time: End of shift. Index: 0.15 g/g creatinine. Ns.  
- Xylene:  
ACGIH - BEI: Determinant: Methylhippuric acids in urine. Sampling Time: End of shift. Index: 1.50 g/g creatinine.  
  
Ns: The determinant is nonspecific, since it is also observed after exposure to other chemicals.

**Other limits and values:**  
- Isobutyl alcohol:  
IDLH (NIOSH, 2010): 1600 ppm.

**Appropriate engineering controls:** Provide mechanical ventilation and direct exhaust system to the outside environment. These measures help reduce the exposure to the product. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.

### Individual protection measures, such as personal protective equipment (PPE)

**Eye/face protection:** Safety glasses.

**Skin protection:** Closed shoes and suitable protective clothing. Appropriate protective gloves.

**Respiratory protection:** A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.

**Thermal hazards:** Does not present thermal hazards.

## 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Aspect:** Liquid, viscous.

**Color:** Not available.

**Odour:** Not available.

**Melting:** Not available.

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 6/10

point/freezing point:

Boiling point or initial

Not available.

boiling point and  
boiling range:

Flammability:

Flammable.

Lower and upper  
explosion  
limit/flammability  
limit:

Not available.

Flash point:

≥ 23 °C (73.4 °F) and ≤ 60 °C (140 °F) - Closed cup.

Auto-ignition  
temperature:

Not available.

Decomposition  
temperature:

Not available.

pH:

Not available.

Kinematic viscosity:

Not available.

Solubility(ies):

Water immiscible.

Partition coefficient n-  
octanol/water (log  
value):

Not available.

Vapour pressure:

Not available.

Relative vapour  
density:

Not available.

Density and/or  
relative density:

Not available.

Particle  
characteristics:

Not applicable.

Other information:

Absolute density: 0.985 to 1 g/cm<sup>3</sup>.

### 10 - STABILITY AND REACTIVITY

Reactivity:

Reactivity is not to be expected under normal conditions of temperature and pressure

Stability:

Stable product under normal conditions of temperature and pressure.

Possibility of  
hazardous reactions:

Xylene: Risk of explosion when in contact with nitric acid and uranium hexafluoride. May react dangerously with oxidizing agents and sulfuric acid. Aluminum: Reacts with water and alcohols, and violently with oxidants, strong acids, strong bases, and chlorinated hydrocarbons, causing fire and explosion hazard. Ethylbenzene: Reacts violently with oxidizing materials. Isobutyl alcohol: May ignite on contact with chromium trioxide. It can react with aluminum at high temperatures, forming hydrogen gas (explosive).

Conditions to avoid:

Elevated temperatures. Contact with incompatible materials.

Incompatible  
material:

Acids, Alcohol, Aluminum, Chlorinated hydrocarbons, Chromium trioxide, Concentrated oxygen, Hydrochloric acid, Nitric acid, Oxidizing Agents, Oxygen, Strong base,

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 7/10

Sulphuric acid and Water.

Hazardous  
decomposition  
products:

There are not known hazardous decomposition products.

### 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:

Product not classified as acute toxic.  
ATEmix Oral: > 5000 mg/kg.  
ATEmix Dermal: > 5000 mg/kg.  
ATEmix Vapours (4h): > 20 mg/L.  
ATEmix Dusts and mists (4h): > 5 mg/L.

Skin  
corrosion/irritation:

Causes skin irritation with redness, pain and dryness.

Serious eye  
damage/irritation:

Causes serious eye irritation with redness and pain.

Respiratory or skin  
sensitization:

It is not expected that the product presents respiratory or skin sensitization.

The ingredient Scinex, classified as skin sensitizer - category 1, is in concentration < 1% and does not contribute to this classification of the product.

Germ cell  
mutagenicity:

It is not expected that the product presents germ cell mutagenicity.

Carcinogenicity:

It is not expected that the product presents carcinogenicity.

The ingredient Scinex, classified as carcinogenic - category 2, is in concentration < 1% and does not contribute to this classification of the product.

Reproductive  
toxicity:

It is not expected that the product presents reproductive toxicity.

STOT - Single  
exposure:

May cause respiratory irritation, may cause cough and sneezing.

Information regarding to :

- Xylene:

At high concentrations may cause hypotension, tachycardia, vasodilation, dizziness, incoordination, headache, confusion, stupor and coma.

STOT - Repeated  
exposure:

It is not expected that the product presents specific target organ toxicity by repeated exposure.

Aspiration Hazard:

It is not expected that the product presents aspiration hazard.

### 12 - ECOLOGICAL INFORMATION

Toxicity:

Very toxic to aquatic life with long lasting effects.

Information regarding to :

- Distillates (petroleum), hydrotreated light:

EC<sub>50</sub> (*Daphnia magna*, 48h): 1.4 mg/L;

LC<sub>50</sub> (*Oncorhynchus mykiss*, 96h): 2-5 mg/L.

- Xylene:

NOEC (*Oncorhynchus mykiss*, 56 d): > 1 mg/L;

NOEC (*Ceriodaphnia dubia*, 7 d): > 1 mg/L;

LC<sub>50</sub> (*Lepomis macrochirus*, 96h): 19 mg/L;

EC<sub>50</sub> (Crustacea, 48h): 8.5 mg/L.

Persistence and

The product presents persistence and it is not considered readily biodegradable.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 8/10

### degradability:

Bioaccumulative potential: Presents low bioacumulative potencial in aquatic organisms.  
Information regarding to :  
- Xylene:  
BCF: 6  
log  $K_{ow}$ : 3.09.

Mobility in soil: Not determined.

Other adverse effects: There are not known other environmental effects for this product.

### 13 - DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### 14 - TRANSPORT INFORMATION

**Road:** UN - United Nations: Model Regulations:  
• Recommendations on the Transport of Dangerous Goods.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: II

**Railway regulations:** COTIF - Convention concerning International Carriage by Rail:  
• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

UN number: 1263

**Sea:** IMO - International Maritime Organization:  
• IMDG Code - International Maritime Dangerous Goods Code.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: II

EmS: F-E,S-E

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01 Date: 01/12/2022 Pages: 9/10

Environmental hazards: The product is considered a marine pollutant.

**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: II

Special precautions for user: Not applicable

### 15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### 16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated October 2018.

#### Change Control:

Version	Elaboration	Changes
01	10/09/2018	Elaboration

#### Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
BCF - Bioconcentration factor;  
BEI - Biological Exposure Index;  
CAS - Chemical Abstracts Service;  
EC - European Community;  
EC<sub>50</sub> - Effective Concentration 50%;  
EEC - European Economic Community;  
IDLH - Immediately Dangerous to Life or Health;

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** BRIGHT METALLIC SYNTHETIC ENAMEL - GOLDEN YELLOW

Revision: 01

Date: 01/12/2022

Pages: 10/10

*K<sub>ow</sub>* - Octanol/Water partition coefficient;  
LC<sub>50</sub> - Lethal Concentration 50%;  
NIOSH - National Institute for Occupational Safety and Health;  
NOEC - No Observed Effect Concentration;  
OSHA - Occupational Safety & Health Administration;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations.

**Bibliographic references:**

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.  
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based  
on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents &  
Biological Exposure Indices (BEIs®). Cincinnati-USA, 2020.

REACH - REGISTRATION, EVALUATION, AUTHORIZATION AND RESTRICTION OF CHEMICALS. Commission  
Regulation (EC) No 1272/2008 of December 2008 amending and repealing Directives 67/548/EEC and  
1999/45/EC, and amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on  
the Registration, Evaluation, Authorization and Restriction of Chemicals. Available at: < <http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:353:0001:1355:en:PDF> >. Access in: Oct. 2018.