

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 1/10

### 1 - IDENTIFICATION

GHS Product identifier:	THINNER 4000
Other means of identification:	001688-00
Recommended use of the chemical:	Industrial use.
Specific restrictions on use:	There are not known restrictions on use of the product.
Supplier's details:	ANJO QUIMICA DO BRASIL LTDA
Address:	Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800, Criciúma - SC - BR
Phone number(s):	(48) 34618000 (48) 34618049
Emergency phone number:	CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

### 2 - HAZARD IDENTIFICATION

Classification of the substance or mixture:	Flammable Liquids - Category 3 Acute Toxicity - Oral - Category 4 Skin Corrosion/Irritation - Category 2 Reproductive Toxicity - Category 1A Specific Target Organ Toxicity -Single Exposure - Category 3 - Narcotic Specific Target Organ Toxicity -Repeated Exposure - Category 1 Hazardous to the Aquatic Environment - Acute Hazard - Category 2 Hazardous to the Aquatic Environment - Chronic Hazard - Category 2
Classification system adopted:	Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:



Signal word: DANGER

Hazard statement(s):  
H226 Flammable liquid and vapour.  
H302 Harmful if swallowed.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H360 May damage fertility or the unborn child.  
H372 Causes damage to the central nervous system through prolonged or repeated exposure.  
H411 Toxic to aquatic life with long lasting effects.

Precautionary statement(s):  
**PREVENTION:**  
P203 Obtain, read and follow all safety instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 2/10

sources. No smoking.  
P233 Keep container tightly closed.  
P240 Ground and bond container and receiving equipment.  
P241 Use explosion-proof electrical, ventilating and lighting equipment.  
P242 Use non-sparking tools.  
P243 Take action to prevent static discharges.  
P260 Do not breathe dust/fume/gas/mist/vapours/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 Wash hands thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

### RESPONSE TO EMERGENCY:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse affected areas with water.  
P304 + P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P318 IF exposed or concerned, get medical advice.  
P319 Get medical help if you feel unwell.  
P321 Specific treatment.  
P330 Rinse mouth.  
P332 + P317 If skin irritation occurs: Get medical help.  
P362 + P364 Take off contaminated clothing. And wash it before reuse.  
P370 + P378 In case of fire: Use carbon dioxide (CO<sub>2</sub>), foam, water mist and powder to extinguish.  
P391 Collect spillage.

### STORAGE:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.  
P403 + P235 Store in a well-ventilated place. Keep cool.  
P405 Store locked up.

### DISPOSITION:

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification:

It is not expected that product presents specific hazards.

## 3 - COMPOSITION/INFORMATION ON INGREDIENTS

### MIXTURE

Components contributing to the hazard:	Toluene (CAS 108-88-3): 42.50 - 100 %; 2-ethoxyethanol (CAS 110-80-5): 7.50 - 22.50 %.
--	---

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 3/10

### 4 - FIRST-AID MEASURES

#### Routes of exposure

Inhalation:	Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.
Skin:	Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.
Eye:	Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.
Ingestion:	Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.
Most important symptoms/effects, acute and delayed:	Causes skin irritation with redness, pain and dryness. Harmful if swallowed. May cause drowsiness or dizziness, may cause dizziness and nausea. Causes damage to the central nervous system through prolonged or repeated exposure.
Indication of immediate medical attention and special treatment needed, if necessary:	Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

### 5 - FIRE-FIGHTING MEASURES

Extinguishing Media:	Appropriate: carbon dioxide (CO <sub>2</sub> ), foam, water mist and powder. Inappropriate: water directly onto the burning product.
Specific hazards arising from the chemical:	The combustion or the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide. Very dangerous when exposed to excessive heat or other sources of ignition such as sparks, open flames or flames of matches and cigarettes, welding operations, pilot lights and electric motors. Can accumulate static charge by flow or agitation. Vapors from heated liquid can be ignited by static discharge. Vapors are heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Can travel great distances causing retrogression of the flame or new fires both in open environments in as confined ones. Containers may explode if heated.
Special protective actions for fire-fighters:	Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

### 6 - ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel:	Prevent sparks or flames. Do not smoke. Do not touch damaged containers or spilled material without the use of appropriate clothing. Avoid exposure to the product. Stay in a safe place, with wind from behind. Use personal protective equipment as described in Section 8.
<b>For emergency</b>	Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 4/10

<b>responders:</b>	closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.
Environmental precautions:	Avoid that the spilled material reaches waterways or sewage system.
Method and materials for containment and cleaning up:	Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material. For final destination, proceed pursuant to Section 13 of this SDS.

### 7 - HANDLING AND STORAGE

#### Precautions for safe handling

Safe handling of the substance or mixture:	Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation. Avoid exposure to the chemical, since the effects may not be felt immediately.
General hygiene:	Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom. Contaminated clothing should be changed and washed before reuse. Remove clothing and protective equipment contaminated before entering eating areas.

#### Conditions for safe storage, including any incompatibilities

Technical measures for prevention of fire and explosion:	Keep away from heat, sparks, open flames and hot surfaces. - Do not smoke. Keep container tightly closed. Ground the container vessel and the receiver of the product during transfers. Only use anti-sparking tools. Avoid the accumulation of electrostatic charges. Use electrical equipment, ventilation and lighting explosion proof. Use personal protective equipment as described in Section 8.
Adequate conditions:	Store in a well ventilated place, away from sunlight. Keep container closed. Keep away from high temperatures and ignition sources. Keep stored at room temperature not exceeding 35°C (95°F).
Packaging compatibilities:	Similar to the original packaging.
Inadequate packaging materials:	There are not known unsuitable material of the product.

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Occupational exposure limit:	The values below apply to workplaces. <ul style="list-style-type: none"> <li>- <u>2-ethoxyethanol:</u> OSHA - PEL - TWA: 200 ppm; 740 mg/m<sup>3</sup>; NIOSH - REL - TWA: 0.5 ppm; ACGIH - TLV - TWA: 5 ppm.</li> <li>- <u>Toluene:</u> OSHA - PEL - TWA: (Z2);</li> </ul>
------------------------------	--

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 5/10

NIOSH - REL - TWA: 375 mg/m<sup>3</sup>; 100 ppm;  
NIOSH - REL - STEL: 560 mg/m<sup>3</sup>; 150 ppm;  
ACGIH - TLV - TWA: 20 ppm.

Z2: See NIOSH REL Annotated Z-2.

**Biological limit:**

- 2-ethoxyethanol:

ACGIH - BEI: Determinant: 2-Ethoxyacetic acid in urine. Sampling Time: End of shift at end of workweek. Index: 100.00 mg/g creatinine.

- Toluene:

ACGIH - BEI: Determinant: o-Cresol in urine. Sampling Time: End of shift. Index: 0.30 mg/g creatinine. B; Determinant: Toluene in blood. Sampling Time: Prior to last shift of workweek. Index: 0.02 mg/L; Determinant: Toluene in urine. Sampling Time: End of shift. Index: 0.03 mg/L.

B: The determinant may be present in biological specimens collected from subjects who have not been occupationally exposed, at a concentration which could affect the interpretation of the results. Such background concentrations are incorporated in the BEI value.

**Other limits and values:**

Not established.

**Appropriate engineering controls:**

Provide mechanical ventilation and direct exhaust system to the outside environment. These measures help reduce the exposure to the product. Maintain atmospheric concentrations, of the constituents of the product, below the indicated occupational exposure limits. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.

**Individual protection measures, such as personal protective equipment (PPE)**

**Eye/face protection:** Safety glasses.

**Skin protection:** Closed shoes and suitable protective clothing. Appropriate protective gloves.

**Respiratory protection:** A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.

**Thermal hazards:** Does not present thermal hazards.

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

**Aspect:** Liquid.

**Color:** Not available.

**Odour:** Not available.

**Melting point/freezing point:** Not available.

**Boiling point or initial boiling point and boiling range:** Not available.

**Flammability:** Flammable.

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04 Date: 01/24/2022 Pages: 6/10

Lower and upper explosion limit/flammability limit:	Not available.
Flash point:	≥ 23 °C (73.4 °F) and ≤ 60 °C (140 °F) - Closed cup.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
pH:	Not available.
Kinematic viscosity:	Not available.
Solubility(ies):	Partially miscible with water.
Partition coefficient n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Relative vapour density:	Not available.
Density and/or relative density:	0.86 to 0.9 (water at 4°C=1) at 25 °C.
Particle characteristics:	Not applicable.
Other information:	Not applicable.

### 10 - STABILITY AND REACTIVITY

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure
Stability:	Product is stable under normal conditions of temperature and pressure.
Possibility of hazardous reactions:	Xylene: Risk of explosion when in contact with nitric acid and uranium hexafluoride. You could dangerously react with oxidizing agents and sulfuric acid. 2-ethoxyethanol: The substance can form explosive peroxides. Reacts with strong oxidants with risk of fire and explosion.
Conditions to avoid:	Elevated temperatures. Sources of ignition. Contact with incompatible materials.
Incompatible material:	Copper, Plastic, Rubber, Strong Acids, Strong base and Strong Oxidizing agents.
Hazardous decomposition products:	There are not known hazardous decomposition products.

### 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:	Product not classified as acute toxic by dermal and inhalation. Harmful if swallowed. ATEmix Dermal: > 5000 mg/kg.
-----------------	--

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 7/10

ATEmix Vapours (4h): > 20 mg/L.  
ATEmix Oral: 715,472 mg/kg.

Information regarding to :

- Toluene:

LD<sub>50</sub> Oral (rats): 636 mg/kg.

- 2-ethoxyethanol:

LD<sub>50</sub> Oral (rats): 2451 mg/kg.

**Skin corrosion/irritation:** Causes skin irritation with redness, pain and dryness.

**Serious eye damage/irritation:** It is not expected that the product causes eye irritation.

**Respiratory or skin sensitization:** It is not expected that the product presents respiratory or skin sensitization.

**Germ cell mutagenicity:** It is not expected that the product presents germ cell mutagenicity.

**Carcinogenicity:** It is not expected that the product presents carcinogenicity.

**Reproductive toxicity:** May damage fertility or the unborn child.

**STOT - Single exposure:** May cause drowsiness or dizziness, may cause dizziness and nausea.  
Information regarding to :  
- Toluene:  
At high concentrations may cause hypotension, tachycardia, vasodilation, dizziness, incoordination, headache, confusion, stupor and coma.

**STOT - Repeated exposure:** Causes damage to the central nervous system through prolonged or repeated exposure.  
Information regarding to :  
- Toluene:  
Repeated exposure may cause vision impairment, hearing loss, tremor, ataxia, and amnesia.

**Aspiration Hazard:** It is not expected that the product presents aspiration hazard.

### 12 - ECOLOGICAL INFORMATION

**Toxicity:** Toxic to aquatic life with long lasting effects.  
Information regarding to :  
- Toluene:  
EC<sub>50</sub> (*Daphnia magna*, 48h): 3.78 mg/L;  
LC<sub>50</sub> (*Oncorhynchus kisutch*, 96h): 5.5 mg/L.

**Persistence and degradability:** The product does not present persistence and it is considered readily biodegradable.  
Information regarding to :  
- Toluene:  
Aerobic degradation rate: 74% in 10 days.  
- 2-ethoxyethanol:  
Degradation rate: 63% in 14 days.

**Bioaccumulative potential:** Presents high bioaccumulative potencial in aquatic organisms.  
Information regarding to :  
- Toluene:

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04 Date: 01/24/2022 Pages: 8/10

BCF: 90000  
log  $K_{ow}$ : 2730.

Mobility in soil: Not determined.

Other adverse effects: There are not known other environmental effects for this product.

### 13 - DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### 14 - TRANSPORT INFORMATION

**Road:** UN - United Nations: Model Regulations:  
• Recommendations on the Transport of Dangerous Goods.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: III

**Railway regulations:** COTIF - Convention concerning International Carriage by Rail:  
• Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

UN number: 1263

**Sea:** IMO - International Maritime Organization:  
• IMDG Code - International Maritime Dangerous Goods Code.

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: III

EmS: F-E,S-E

Environmental hazards: The product is considered a marine pollutant.

**Air:** IATA - International Air Transport Association:  
• DGR - Dangerous Goods Regulation.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04 Date: 01/24/2022 Pages: 9/10

UN number: 1263

Proper shipping name: PAINT RELATED MATERIAL

Primary risk class or division: 3

Subsidiary risk class or division: NA

Packing group: III

Special precautions for user: Not applicable

### 15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### 16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated January 2022.

#### Change Control:

Version	Elaboration	Changes
04	01/24/2022	Change in composition. Change in section: 1, 2, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15 and 16.

#### Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;  
 ATEmix - Acute Toxicity Estimate of the mixture;  
 BCF - Bioconcentration factor;  
 BEI - Biological Exposure Index;  
 CAS - Chemical Abstracts Service;  
 EC - European Community;  
 EC<sub>50</sub> - Effective Concentration 50%;  
 EEC - European Economic Community;  
 IARC - International Agency for Research on Cancer;  
 K<sub>ow</sub> - Octanol/Water partition coefficient;  
 LC<sub>50</sub> - Lethal Concentration 50%;  
 LD<sub>50</sub> - Lethal Dose 50%;

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** THINNER 4000

Revision: 04

Date: 01/24/2022

Pages: 10/10

NIOSH - National Institute for Occupational Safety and Health;  
OSHA - Occupational Safety & Health Administration;  
PEL - Permissible Exposure Limit;  
REL - Recommended Exposure Limit;  
STEL - Short Term Exposure Limit;  
TLV - Threshold Limit Value;  
TWA - Time Weighted Average;  
UN - United Nations.

**Bibliographic references:**

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.  
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based  
on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents &  
Biological Exposure Indices (BEIs®). Cincinnati-USA, 2020.

ECHA - EUROPEAN CHEMICAL AGENCY. Available at: < <http://echa.europa.eu/web/guest> >. Access in: Jan.  
2022.

GESTIS - SUBSTANCE DATABASE. Available at: < [http://gestis-  
en.itrust.de/nxt/gateway.dll/gestis\\_en/000000.xml?f=templates\\$fn=default.htm\\$3.0](http://gestis-en.itrust.de/nxt/gateway.dll/gestis_en/000000.xml?f=templates$fn=default.htm$3.0) >. Access in: Jan.  
2022.

HSDB - HAZARDOUS SUBSTANCES DATA BANK. Available at: <http://pubchem.ncbi.nlm.nih.gov/>. Access in:  
Jan. 2022.

IARC - INTERNATIONAL AGENCY FOR RESEARCH ON CANCER. Available at:  
<http://monographs.iarc.fr/ENG/Classification/index.php>. Access in: Jan. 2022.

IPCS - INTERNATIONAL PROGRAMME ON CHEMICAL SAFETY - INCHEM. Available at: <http://www.inchem.org/>.  
Access in: Jan. 2022.

IUCLID - INTERNATIONAL UNIFORM CHEMICAL INFORMATION DATABASE. [S.1.]: European chemical Bureau.  
Available at: <http://ecb.jrc.ec.europa.eu>. Access in: Jan. 2022.

NIOSH - NATIONAL INSTITUTE OF OCCUPATIONAL AND SAFETY. International Chemical Safety Cards.  
Available at: <http://www.cdc.gov/niosh/>. Access in: Jan. 2022.

REACH - REGISTRATION, EVALUATION, AUTHORIZATION AND RESTRICTION OF CHEMICALS. Commission  
Regulation (EC) No 1272/2008 of December 2008 amending and repealing Directives 67/548/EEC and  
1999/45/EC, and amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on  
the Registration, Evaluation, Authorization and Restriction of Chemicals. Available at: < [http://eur-  
lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:353:0001:1355:en:PDF](http://eur-lex.europa.eu/LexUriServ/LexUriServ.do?uri=OJ:L:2008:353:0001:1355:en:PDF) >. Access in: Jan. 2022.

TOXNET - TOXICOLOGY DATA NETWORKING. ChemIDplus Lite. Available at: <http://chem.sis.nlm.nih.gov/>.  
Access in: Jan. 2022.