

Medium Texture

Medium Texture is a water-repellent acrylic finish that allows for the creation of different effects. It is a product that is easy to apply, dries quickly, adheres well and its water repellency helps prevent the entry of water, protecting the surface against infiltrations, making it more resistant.

This product complies with ABNT NBR 11702 type 4.6.2

USE RECOMMENDATIONS

Indicated for texturing external and internal surfaces of plaster, apparent concrete, fiber cement and painted walls, providing resistance to alkalinity, easy application, excellent adherence and high consistency.

BASIC PROPERTIES

Colors	White
Finish	Matte
Solids per Mass	74% ± 2
Solids per Volume	39% ± 2
VOC	5 – 10 g/L
Specific Weight at 25°C	1.86 g/cm ³ (approximate value)
pH	8.0 – 9.0
Flash Point	Not applicable
Storage time	24 months
Toxicity	Consult MSDS
Packaging	6 kg and 23 kg

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

APPLICATION DATA

Recommended number of coats	1 coat
Thickness per coat:	The thickness of the texture will depend on the type of application and the effect to be achieved.
Theoretical spreading rate:	Up to 6 m ² - 6 kg gallon Up to 23 m ² - 23 kg bucket Comments: The practical spreading rate may vary depending on the application method and technique, as well as roughness, absorption, surface conditions and the layer of product applied.
Dilution:	Ready to use. If necessary, dilute the product in at most 10% with water.

DRYING

Temperature	25°C
To touch	4 hours
Final	24 hours

Comments: Drying may vary depending on the thickness of the layer to be applied.

Considerations: Do not paint on rainy days, at temperatures below 10°C or above 35°C or humidity above 80%. The painted surface can only be washed (cleaned) 30 days after its application. The painted surface should be cleaned with water and neutral detergent, soft sponge or cloth. The texture cannot be exposed without finishing paint for more than 7 days.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

SURFACE PREPARATION - ABNT NBR 13245 Standard

The surface must be dry, firm and dust free, free of contaminants such as: oils, salts, grease, fat, dust, etc., duly applied with the recommended primer.

Loose or poorly adhered parts must be scraped and/or brushed.

On aged paint, sand superficially, leaving the surface free from shine and removing loose particles. Before starting painting, observe the following instructions:

TYPE OF SURFACE	TREATMENT
New plaster	Wait for drying and curing (minimum 28 days).
New concrete	Wait for drying and curing (minimum 28 days). Apply Anjo Wall Primer (see product dilution).
Fiber cement	Apply Anjo Wall Primer (see product dilution).
Weak plaster	Wait for drying and curing (minimum 28 days). Apply Anjo Wall Primer (see product dilution).
Whitewashed surfaces or with loose or poorly adhered particles	Scrape and/or brush the surface, eliminating loose parts. Apply Anjo Wall Primer (see product dilution).
Fat or grease stains	Wash with water and detergent, rinse and wait for drying.
Moldy parts	Wash with bleach and water at a 1:1 ratio, rinse and wait for drying.

APPLICATION METHOD

The application must be carried out with a textured roller, and its finish will depend on the layer applied, the spreading, and the thickness of the material.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

APPLICATION INSTRUCTIONS

Before starting any painting, always pay attention to the following procedure:

Sand the surface: sanding the surface is required, removing loose parts and promoting greater adhesion to the product that will be subsequently applied.

Clean: Clean with a cloth or broom to remove dust from the surface and ensure adherence of the product that will be applied to the surface.

Seal: The use of sealer evens out surface absorption, in addition to significantly improving the spreading rate of the product to be applied.

Homogenize: Homogenization is required for the complete mixing of all components. As the product will be kept in stock, this operation is indispensable for the characteristics to remain unchanged.

Dilute: dilution must observe the recommended instructions, so that the product can offer excellent performance such as coverage, spreading rate, leveling and application.

Apply: always pay attention to loose or badly adhered parts of the substrate, in these cases, the surface preparation recommendations must be observed.

Sanding: If the work to be performed with the texture requires sanding, use sandpaper with a grain size between 180# - 220#.

RECOMMENDED PRIMER

Wall primer

Pigmented acrylic sealer

For others, consult our Technical Department

SAFETY RECOMMENDATION

- Store the product in closed, ventilated environments with maximum temperatures of 40°C.
- When applied, the product emits vapors that must be avoided with the correct use of PPE, such as masks and respirators, ensuring proper ventilation during application.
- Avoid skin contact using gloves, goggles, suitable garments, protective creams, etc.
- Keep away from children and animals.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.

COMMENTS

In order to provide and ensure the quality of the products, it is essential to use our complete Anjo painting system (bases, putties, thinners and finishes) observing the instructions contained on the packaging or in the technical report.

Do not store the diluted product. Do not use different batches to continue painting, there may be a change in tone, as well as in the finish.

The spreading rate of this product will vary according to the type of surface and the painting system to be used, the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The values found for the specific weight and drying tests (with the specified thickness) were obtained in the laboratory at a temperature of 25°C. With temperatures other than those mentioned, the values established above tend to be different from those specified.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

The use of solvents other than those specified without prior approval from Anjo may affect product performance and void product warranty.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.

This information represents the best of our knowledge when this document was published. We remind you that optimal final results when applying the products depend on factors that exceed our control and that concern the surface preparation and the technical knowledge of the applicator. The company reserves the right to change these specifications without prior notice.