

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 1/8

### 1 - IDENTIFICATION

GHS Product identifier:	Waterborne Armored Floor Anti Slip Graphene - Red
Other means of identification:	047275-00
Recommended use of the chemical:	Application on floors.
Specific restrictions on use:	There are not known restrictions on use of the product.
Supplier`s details:	ANJO QUIMICA DO BRASIL LTDA
Address:	Acesso Estadual Rio Maina, nº 1165, Bairro Vila Macarini CEP: 88818-800 - SC - BRA
Phone number(s):	(48) 34618000 (48) 34618049
Emergency phone number:	CIATox/SC (Centro de Informação e Assistência Toxicológica de Santa Catarina) 08006435252

### 2 - HAZARD IDENTIFICATION

Classification of the substance or mixture:	Skin Corrosion/Irritation - Category 3 Serious eye damage/eye irritation - Category 2A Skin Sensitization - Category 1
Classification system adopted:	Globally Harmonized System of Classification and Labeling of Chemicals (GHS), United Nations.

#### GHS label elements, including precautionary statements

Pictograms:



Signal word: WARNING

Hazard statement(s):  
H316 Causes mild skin irritation.  
H317 May cause an allergic skin reaction.  
H319 Causes serious eye irritation.

Precautionary statement(s):  
**PREVENTION:**  
P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
P264 + P265 Wash hands thoroughly after handling. Do not touch eyes.  
P272 Contaminated work clothing should not be allowed out of the workplace.  
P280 Wear protective gloves, protective clothing, eye protection, face protection and hearing protection.

#### RESPONSE TO EMERGENCY:

P302 + P352 IF ON SKIN: Wash with plenty of water.  
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P321 Specific treatment.  
P332 + P317 If skin irritation occurs: Get medical help.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 2/8

P333 + P317 If skin irritation or rash occurs: Get medical help.  
P337 + P317 If eye irritation persists: Get medical help.  
P362 + P364 Take off contaminated clothing and wash it before reuse.

**DISPOSITION:**

P501 Dispose of contents and container in accordance with local regulations.

Other hazards which do not result in classification: The product has no other hazards.

### 3 - COMPOSITION/INFORMATION ON INGREDIENTS

**MIXTURE**

Components contributing to the hazard:

- Quartz (CAS 14808-60-7): 5.92 - 6.04 % <sup>1</sup>;
- Titanium dioxide (CAS 13463-67-7): 2.97 - 3.03 % <sup>1</sup>;
- ESPESSANTE ACRILICO (CAS Not applicable): 1.19 - 1.21 %;
- Fenilpoliglicoleter (CAS 122-99-6): 0.70 - 0.71 %;
- KAOLIN (CAS 1332-58-7): 0.50 % <sup>1</sup>;
- Sodium metasilicate (CAS 6834-92-0): 0.23 %;
- 3- glycidylxypropyl - trimethylsiloxane (CAS 2530-83-8): 0.15 %;
- Nonylphenol (CAS 9016-45-9): 0.10 %;
- Triethanolamine 85% (CAS 102-71-6): 0.04 % <sup>2</sup>;
- Morpholine (CAS 110-91-8): 0.04 %.

<sup>1</sup> Ingredient not classified as hazardous by the Classification System used, but has an established occupational exposure limit, according to section 8.

<sup>2</sup> The ingredient does not contribute to the hazard but has an established occupational exposure limit, according to section 8.

### 4 - FIRST-AID MEASURES

**Description of necessary first-aid measures**

**Inhalation:** Remove victim to fresh air and keep at rest in a position comfortable for breathing. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Skin:** Wash exposed skin with sufficient amount of water to remove the material. Take off and isolate contaminated clothing and shoes. In case of skin irritation: contact a doctor. Bring this SDS.

**Eye:** Wash carefully with water for several minutes. In case of use of contact lenses, remove them, if possible. Keep washing. If eyes irritation continues: Contact a doctor. Bring this SDS.

**Ingestion:** Do not induce vomiting. Never give anything by mouth to an unconscious person. Rinse the victims mouth with water in abundance. If the victim feels unwell, contact a TOXICOLOGICAL INFORMATION CENTER or a doctor. Bring this SDS.

**Most important symptoms/effects, acute and delayed:** May cause an allergic skin reaction with pruritus and dermatitis. Causes mild skin irritation with redness and dryness. Causes serious eye irritation with redness and pain.

**Indication of immediate medical** Avoid contact with the product to help the victim. Keep victim warm and quiet. Symptomatic treatment should comprise mainly supportive measures such as

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 3/8

attention and special treatment needed, if necessary: correction of electrolyte disturbances, metabolic, and respiratory support. In case of skin contact do not rub the affected area.

### 5 - FIRE-FIGHTING MEASURES

**Extinguishing media:** Appropriate: carbon dioxide (CO<sub>2</sub>), foam, water mist and powder.  
Inappropriate: water jet directly.

**Specific hazards arising from the chemical:** The combustion of the chemical containers may form toxic and irritant gases such as carbon monoxide and carbon dioxide.  
Vapors may be heavier than air and tend to accumulate in low or confined areas, such as sewers and basements. Containers may explode if heated.

**Special protective actions for fire-fighters:** Use self-contained breathing apparatus (SCBA) operated in positive pressure mode and complete protective clothing. Containers and tanks involved in the fire should be cooled with water mist.

### 6 - ACCIDENTAL RELEASE MEASURES

#### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel:** Do not smoke. Avoid exposure to the product. If necessary, use personal protective equipment as described in Section 8.

**For emergency responders:** Wear complete PPE with safety glasses, safety gloves, suitable protective clothing and closed shoes. In case of leakage, where exposure is high, it is recommended to use a suitable respiratory protection mask.

**Environmental precautions:** Avoid that the spilled material reaches waterways or sewage system.

**Methods and materials for containment and cleaning up:** Use water mist or vapor suppressing foam to reduce the dispersion of vapors. Use natural barriers or spill containment. Collect spilled material and put it into containers. Adsorb the remaining product with dried sand, vermiculite or any other inert material. Put the adsorbed material in appropriate containers and remove them to a safe place. Use tools that do not cause sparks to collect absorbed material.

### 7 - HANDLING AND STORAGE

#### Precautions for safe handling

**Precautions for safe handling:** Handle in a well ventilated area or with general system of ventilation/local exhaust. Avoid vapors and mists formation.

**General hygiene:** Wash hands and face thoroughly after handling and before eating, drinking, smoking or going to the bathroom.

#### Conditions for safe storage, including any incompatibilities

**Technical measures for prevention of fire and explosion:** It is not expected that the product presents a fire or explosion hazard. Use personal protective equipment as described in Section 8.

**Conditions for safe storage, including any incompatibilities:** Store in a well ventilated place away from sunlight. Keep container closed. Keep away from high temperatures.

**Packaging compatibilities:** Similar to the original packaging.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 4/8

Inadequate packaging materials: There are not known unsuitable material of the product.

### 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Control parameters

Occupational exposure limit: The values below apply to workplaces.

- Triethanolamine 85%:  
ACGIH - TLV - TWA: 5 mg/m<sup>3</sup>.
- Morpholine:  
OSHA - PEL - TWA: 20 ppm; 70 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 20 ppm;  
NIOSH - REL - STEL: 30 ppm;  
ACGIH - TLV - TWA: 20 ppm.
- KAOLIN:  
OSHA - PEL - TWA: 15 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);  
NIOSH - REL - TWA: 10 mg/m<sup>3</sup> (TD); 5 mg/m<sup>3</sup> (R);  
ACGIH - TLV - TWA: 2 mg/m<sup>3</sup> (E; R).
- Titanium dioxide:  
OSHA - PEL - TWA: 15 mg/m<sup>3</sup>;  
NIOSH - REL - TWA: 2.4 mg/m<sup>3</sup> (fine); 0.3 mg/m<sup>3</sup> (ultrafine); (Ca) (ultrafine particles); (AA); (B63);  
ACGIH - TLV - TWA: Nanoscale particles 0.2 mg/mL (R); Finescale partiles 2.5 mg/mL (R).
- Quartz:  
OSHA - PEL - TWA: (CFR1);  
NIOSH - REL - TWA: 0.05 mg/m<sup>3</sup> (Ca); (AA);  
ACGIH - TLV - TWA: 0.025 mg/m<sup>3</sup> (R).

TD: Total dust;  
E: The value is for particulate matter containing no asbestos and < 1% crystalline silica;  
R: Respirable particulate matter;  
Ca: Potential occupational carcinogen.  
B63: See NIOSH Intelligence Bulletin 63;  
AA: See NIOSH REL Appendix A;  
CFR1: See CFR 1910.1053.

Biological limit: Not established.

Other limits and values: Not established.

Appropriate engineering controls: Promote mechanical ventilation and exhaust system to outside. These acts help reducing the exposition to the product. Maintain atmospheric concentrations of the constituents of the product below occupational exposure limits indicated.

#### Individual protection measures, such as personal protective equipment (PPE)

Eye/face protection: Safety glasses.

Skin protection: Closed shoes and suitable protective clothing. Appropriate protective gloves.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 5/8

Respiratory protection:	A risk assessment should be performed for proper definition of respiratory protection, in view of the product use conditions.
Thermal hazards:	It does not present thermal hazards.

### 9 - PHYSICAL AND CHEMICAL PROPERTIES

Aspect:	Liquid.
Color:	Not available.
Odour:	Not available.
Melting point/freezing point:	Not available.
Boiling point or initial boiling point and boiling range:	Not available.
Flammability:	Not available.
Lower and upper explosion limit/flammability limit:	Not available.
Flash point:	Not available.
Auto-ignition temperature:	Not available.
Decomposition temperature:	Not available.
pH:	Not available.
Kinematic viscosity:	Not available.
Solubility(ies):	Miscible in water.
Partition coefficient n-octanol/water (log value):	Not available.
Vapour pressure:	Not available.
Relative vapour density:	Not available.
Density and/or relative density:	Not available.
Particle characteristics:	Not applicable.
Other information:	Absolute density: 1.328 g/cm <sup>3</sup> at 25 °C (77 °F).

### 10 - STABILITY AND REACTIVITY

Reactivity:	Reactivity is not to be expected under normal conditions of temperature and pressure.
-------------	---

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01 Date: 03/02/2023 Pages: 6/8

Chemical stability:	Product is stable under normal conditions of temperature and pressure.
Possibility of hazardous reactions:	Triethanolamine 85%: May react dangerously with oxidizing agents, reducing agents, acids, halogenated compounds, metal hydrides and nitriles. Morpholine: Risk of explosion on contact with nitromethane.
Conditions to avoid:	Elevated temperatures. Contact with incompatible materials.
Incompatible material:	Carbon oxides.
Hazardous decomposition products:	There are no known hazardous decomposition products.

### 11 - TOXICOLOGICAL INFORMATION

Acute toxicity:	Product not classified as acute toxic. ATEmix Oral: > 5000 mg/kg. ATEmix Dermal: > 5000 mg/kg. ATEmix Vapours (4h): > 20 mg/L. ATEmix Dusts and mists (4h): > 5 mg/L.
Skin corrosion/irritation:	Causes mild skin irritation with redness and dryness.
Serious eye damage/irritation:	Causes serious eye irritation with redness and pain.
Respiratory or skin sensitization:	May cause an allergic skin reaction with pruritus and dermatitis. Not expected to cause respiratory sensitization.
Germ cell mutagenicity:	It is not expected to show mutagenicity in germ cells.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to be reproductively toxic.
STOT - Single exposure:	Not expected to exhibit specific target organ toxicity by single exposure.
STOT - Repeated exposure:	Not expected to exhibit specific target organ toxicity on repeated exposure.
Aspiration hazard:	Not expected to present an aspiration hazard.

### 12 - ECOLOGICAL INFORMATION

Toxicity:	It is not expected that the product presents ecotoxicity.
Persistence and degradability:	It is not expected to present persistence and degradability.
Bioaccumulative potential:	The product is not expected to have a high bioaccumulative potential.
Mobility in soil:	Not determined.
Other adverse effects:	There are not known other environmental effects for this product.

In accordance with Globally Harmonized System of Classification and Labelling of Chemicals (GHS)- Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 7/8

### 13 - DISPOSAL CONSIDERATIONS

#### Disposal methods

Must be disposed of as hazardous waste in compliance with local regulations. The treatment and disposal should be evaluated for each specific product.  
Keep the product remains in its original and properly closed containers. Disposal should be performed as established for the product.

### 14 - TRANSPORT INFORMATION

<b>Road:</b>	UN - United Nations: Model Regulations: • Recommendations on the Transport of Dangerous Goods.
<b>Railway regulations:</b>	COTIF - Convention concerning International Carriage by Rail: • Appendix C: RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.
<b>Sea:</b>	IMO - International Maritime Organization: • IMDG Code - International Maritime Dangerous Goods Code.
<b>Air:</b>	IATA - International Air Transport Association: • DGR - Dangerous Goods Regulation.
<b>UN number:</b>	Not classified as hazardous to transport in different modals.
<b>Special precautions for user:</b>	Not applicable.

### 15 - REGULATORY INFORMATION

Convention concerning Safety in the use of Chemicals at Work (Convention 170) - International Labour Organization, 1990.

### 16 - OTHER INFORMATION

This SDS was prepared based on current knowledge about the proper product handling and under normal conditions of use, in accordance with the application specified on the packaging. Any other use of the product involving their combination with other materials, and use various forms of those indicated, are the responsibility of the user. Warns that the handling of any chemical substance requires the prior knowledge of its hazards for the user. In the workplace it is for the user company's product promotes training of its collaborators about the possible risks arising from exposure to the chemical.

Elaborated March 2023.

#### Change control:

Version	Elaboration	Changes
01	03/02/2023	Elaboration

#### Abbreviations:

ACGIH - American Conference of Governmental Industrial Hygienists;  
ATEmix - Acute Toxicity Estimate of the mixture;  
CAS - Chemical Abstracts Service;  
NIOSH - National Institute for Occupational Safety and Health;

In accordance with Globally Harmonized System of  
Classification and Labelling of Chemicals (GHS)-  
Chapter 1.5 and Annex 4

## SAFETY DATA SHEET

**Product:** Waterborne Armored Floor Anti Slip Graphene - Red

Revision: 01

Date: 03/02/2023

Pages: 8/8

OSHA - Occupational Safety & Health Administration;

PEL - Permissible Exposure Limit;

REL - Recommended Exposure Limit;

STEL - Short Term Exposure Limit;

TLV - Threshold Limit Value;

TWA - Time Weighted Average;

UN - United Nations.

**Bibliographic references:**

GHS - GLOBALLY HARMONIZED SYSTEM OF CLASSIFICATION AND LABELLING OF CHEMICALS. 8th rev. ed.  
New York: United Nations, 2019.

ACGIH - AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIALS HYGIENISTS. TLVs® and BEIs®: Based  
on the Documentation of the Threshold Limit Values (TLVs®) for Chemical Substances and Physical Agents &  
Biological Exposure Indices (BEIs®). Cincinnati-USA, 2022.