



TECHNICAL NOTICE

2000 UNIVERSAL MATTE AGENT

Usage description:

Indicated for reducing the glossiness of products from the Anjo lines:

- ❖ Synthetic enamel
- ❖ NC Lacquer
- ❖ Polyurethane Varnish HS
- ❖ Polyurethane Varnish MS
- ❖ Fast Polyurethane Varnish
- ❖ Anjodur Polyurethane
- ❖ Anjomix Polyurethane

Composition:

Mineral fillers, solvents and additives.

Supply packaging:

Available in 900ml packaging.

Expiration:

60 months.

Basic information:

- ❖ The component to which 2000 UNIVERSAL MATTE AGENT will be added must be thoroughly homogenized before mixing.
- ❖ After adding 2000 UNIVERSAL MATTE AGENT, the mixture must be homogenized very well again.
- ❖ The 2000 MATTE AGENT must be added before the catalysis and/or dilution of the product, and afterwards only the catalysis, and homogenize very well.
- ❖ The catalysis must always consider only the component A (paint or varnish) without the 2000 UNIVERSAL MATTE AGENT.
- ❖ Thinner must be the last product to be added to the mixture. 2000 UNIVERSAL MATTE AGENT provides a significant reduction in viscosity, therefore the viscosity must be evaluated before adding the thinner to prevent the viscosity from being reduced too much, preventing the application.

Volume to be added of 2000 MATTE AGENT in relation to paint or varnish, according to the desired glossiness:

Product	Semi Gloss	Matte
Anjo Polyurethane Varnish HS	30%	60%
Anjo Fast Polyurethane Primer	20%	50%
Anjo Polyurethane Varnish MS	20%	40%
Anjo NC Lacquer	10%	20%
Anjo Polyurethane Paint (TP or MX)	30%	60%
Anjo Synthetic Enamel	15%	30%

Surface preparation:

Consult the technical notice of the product in which it will be used.

Application:

Consult the technical notice of the product in which it will be used.

Drying:

Consult the technical notice of the product in which it will be used.

Safety recommendations:

Before handling this product, it is essential to carefully read all the information contained in its material safety data sheet (MSDS), available on our website or request it directly from our Customer Service (0800 487 777).

Surface preparation, handling and use of paint during painting and drying, since these are flammable products, must be carried out in ventilated spaces, away from flames, sparks or excessive heat, using the personal protective equipment (PPE) appropriate for the step to be performed. Contact with the skin can cause irritation.

If ingested, do not induce vomiting. In case of contact with eyes, rinse thoroughly with water. In either case, seek medical attention immediately.

Do not smoke in the work area.

Make sure that the electrical installations are perfect and do not produce sparks. Do not use thinner to clean the skin, hands or other parts of the body. To clean hands use alcohol, then wash with water and appropriate cleaning pastes.

In case of fire, use CO2 or chemical powder extinguishers. It is not recommended to use water to extinguish the fire produced by burning paint.

The storage of paints and thinners must be done in ventilated places and protected from weathering. The temperature can range from 10 to 40°C.

If symptoms of intoxication occur due to the inhaling of chemical vapors, the intoxicated person must be immediately removed from the workplace to ventilated

areas.

In case of fainting, call a doctor immediately.

Product intended for use and handling by professionals connected to the painting industry. The application and use of this product must be carried out in accordance with all National Health, Safety and Environmental standards and regulations.

If it is necessary to remove the already applied and hardened paint from the substrate, the operator and individuals in the same environment must use the appropriate personal protective equipment (PPE) as indicated in the material safety data sheet (MSDS).

Comments:

The spreading rate of this product in practice will vary according to the thickness applied, method and application technique, the type and roughness of the substrate and environmental conditions, etc.

The values found for the drying tests were obtained in the laboratory at a temperature of 25°C and at 60% relative humidity. In temperatures other than those mentioned, the values established above tend to be different from those specified.

The instructions contained in these specifications are based on our experience and technical knowledge; however, some factors are beyond our control as a manufacturer, such as: surface preparation, application, working conditions, etc.

The use of Thinners and Catalysts other than those specified without prior approval from Anjo may affect product performance and void product warranty.

We take no responsibility for material and personal damage caused by the misuse of the information contained in these specifications and of the products mentioned.

These specifications are subject to change without prior notice.